# T2R2 東京科学大学 リサーチリポジトリ Science Tokyo Research Repository

## 論文 / 著書情報 Article / Book Information

題目(和文)	   高速な時間領域境界要素法及びその非線形超音波シミュレーションへ   の適用			
Title(English)	Fast time-domain boundary element method and its application to nonlinear ultrasonic simulation			
著者(和文)	丸山泰蔵			
Author(English)	Taizo Maruyama			
出典(和文)	学位:博士(工学), 学位授与機関:東京工業大学, 報告番号:甲第10240号, 授与年月日:2016年3月26日, 学位の種別:課程博士, 審査員:廣瀬 壮一,天谷 賢治,三上 貴正,アニール ワイジェ,中村 隆志,斎 藤 隆泰			
Citation(English)	Degree:Doctor (Engineering), Conferring organization: Tokyo Institute of Technology, Report number:甲第10240号, Conferred date:2016/3/26, Degree Type:Course doctor, Examiner:,,,,,			
学位種別(和文)	博士論文			
Category(English)	Doctoral Thesis			
種別(和文)				
Type(English)	Summary			

### 論 文 要 旨

THESIS SUMMARY

専攻: Department of	情報環境学(社会・環境 系)	専攻	申請学位(専攻分野): Academic Degree Requested	博士 Doctor of	(工学)
学生氏名: Student's Name	丸山 泰蔵		 指導教員(主): Academic Advisor(main)	教授	廣瀬 壮一
			 指導教員(副): Academic Advisor(sub)		

#### 要旨(英文 800 語程度)

Thesis Summary (approx.800 English Words )

In this dissertation, a convolution quadrature time-domain boundary element method (CQ-BEM) has been accelerated using a fast multipole method (FMM) and a rapid convolution algorithm for solving large-scale wave problems. The author has applied the proposed fast CQ-BEM to numerical simulations of nonlinear ultrasonic testing (NLUT) based on the contact acoustic nonlinearity (CAN). He also investigated causes and characteristics of the nonlinear phenomenon from obtained numerical results.

This dissertation is organized by the following seven chapters:

#### Chapter 1 [Introduction]

The previous studies on the NLUT based on CAN and time-domain BEM including the CQ-BEM were reviewed in Chapter 1. The author then mentioned the importance and requirement of theoretical approach to nonlinear ultrasonic phenomena. He also pointed out the limitations of conventional time-domain BEM for wave problems. The organization of this dissertation is also described in this chapter.

#### Chapter 2 [Convolution Quadrature Time-domain Boundary Element Method (CQ-BEM)]

Although the time-domain BEM is considered as the most appropriate numerical method for the nonlinear ultrasonic simulation, the conventional one in which a collocation method is used for time discretization has disadvantages in its numerical stability. Therefore, as the solution of this issue, the CQ-BEM based on implicit Runge-Kutta scheme (IRK-based CQ-BEM) has been proposed. Its important aspects were presented through numerical examples for three-dimensional (3-D) acoustic wave problems. Then, the author pointed out that the computational complexity of the IRK-based CQ-BEM is large, and application of acceleration techniques is often required.

#### Chapter 3 [Acceleration of CQ-BEM]

The IRK-based CQ-BEM has disadvantages in its computational cost, and the original computational and memory complexities are  $O(N^2M^2)$ , where N and M denote the numbers of time steps and elements, respectively. Therefore, the acceleration of CQ-BEM for 3-D acoustic and elastic wave problems using the FMM and rapid convolution algorithm have been presented in Chapter 3. As the result of acceleration, the computational and memory complexities could be reduced to  $O(NM\log N\log M)$  and O(NM), respectively. The accuracy and efficiency of fast CQ-BEM were also confirmed by solving wave problems numerically.

#### Chapter 4 [3-D Simulation of Higher-harmonic Waves Due to an Interface Crack]

From Chapter 4, the application of IRK-based CQ-BEM to nonlinear ultrasonic simulation has been discussed. The 3-D simulation of nonlinear ultrasonic waves due to an interface crack with contact boundary conditions between two semi-infinite elastic solids, has been performed in Chapter 4. This problem can be considered as the wave scattering by a nonlinear imperfection on a bi-material interface. The appropriate boundary element formulation for this problem has been proposed in order to accurately compute the

tangential velocity of displacement which is included in the nonlinear boundary conditions. The author carried out some numerical simulations of the higher-harmonic generation in NLUT and validated the numerical model of interface crack through obtained numerical results.

## Chapter 5 [2-D Simulation of Nonlinear Ultrasonic Waves Due to Interior and Surface Breaking Cracks]

Some 3-D nonlinear ultrasonic simulations were performed in Chapter 4. Since the boundary element formulation was developed for an interface crack between two semiinfinite elastic solids, not only the boundary elements of interface crack but the ones of bimaterial interface were also required. Thus, it is difficult to conduct long-time analyses and to confirm the sub-harmonic generation using the method owing to its computational cost. In Chapter 5, therefore, 2-D long-time analyses of nonlinear ultrasonic generation by interior and surface breaking cracks have been implemented by the non-accelerated CQ-BEM. Complex shape and arrangement of cracks were considered because the multiple reflection of bulk waves is significant to the sub-harmonic generation in view of the previous researches. Moreover, the nearly stationary vibration fields must be investigated to confirm the sub-harmonic generation.

From numerical results, the author succeeded in the numerical simulation of subharmonic generation and investigated the relationship between the nonlinear sub-harmonic resonance and frequency response characteristic of the linear system. It was also found that the behavior of sub-harmonic generation due to a surface breaking crack is different from that due to interior cracks.

#### Chapter 6 [3-D Simulation of Nonlinear Ultrasonic Waves Due to Interior Cracks]

The 3-D simulation of nonlinear ultrasonic waves due to interior cracks has been conducted by the fast CQ-BEM, which is presented in Chapter 3, in order to investigate dimensional effects in the sub-harmonic generation. In practice, the shape and arrangement of cracks have 3-D geometry, and it is important to evaluate the dimensional effect. Therefore, the numerical method that was developed in Chapter 5, has been extended to the 3-D crack problem.

From numerical results, it was confirmed that the sub-harmonic generation is caused under the similar conditions to the 2-D cases. However, the dimensional effect is significant to the characteristic of sub-harmonic generation, and it was hard to observe the sub-harmonic generation compared with the 2-D case.

#### Chapter 7 [Final Remarks]

The author stated the conclusions of this dissertation and mentioned the future prospects.

備考 : 論文要旨は、和文 2000 字と英文 300 語を 1 部ずつ提出するか、もしくは英文 800 語を 1 部提出してください。

Note : Thesis Summary should be submitted in either a copy of 2000 Japanese Characters and 300 Words (English) or 1copy of 800 Words (English).

注意:論文要旨は、東工大リサーチリポジトリ(T2R2)にてインターネット公表されますので、公表可能な範囲の内容で作成してください。 Attention: Thesis Summary will be published on Tokyo Tech Research Repository Website (T2R2).