

論文 / 著書情報
Article / Book Information

題目(和文)	
Title(English)	The Effect of Dynamic Solution Condition on the Failure of FRP Exposed to HCl
著者(和文)	Pradyawong Pradchar
Author(English)	Pradchar Pradyawong
出典(和文)	学位:博士（工学）, 学位授与機関:東京工業大学, 報告番号:甲第10310号, 授与年月日:2016年9月20日, 学位の種別:課程博士, 審査員:久保内 昌敏,伊東 章,淵野 哲郎,森 伸介,青木 才子
Citation(English)	Degree;, Conferring organization: Tokyo Institute of Technology, Report number:甲第10310号, Conferred date:2016/9/20, Degree Type:Course doctor, Examiner:,,,,
学位種別(和文)	博士論文
Category(English)	Doctoral Thesis
種別(和文)	要約
Type(English)	Outline

Outline

Chapter I Introduction

1.1 Introduction

1.1.1 Fiber Reinforced Plastic (FRP)

1.1.2 Fiber reinforcements

1.1.3 Glass fiber

1.1.4 Resin systems of the matrix

1.1.4.1 Polyester resins

1.1.4.2 Epoxies

1.1.4.3 Vinyl esters

1.2 Background and literature review

1.2.1 The failure of FRP chemical tank

1.2.2 Theoretical background

1.2.2.1 Diffusion behavior in polymer

1.2.2.1.1 Fickian diffusion

1.2.2.1.2 Non-Fickian diffusion

1.2.2.1.3 Cyclic solution temperature

1.2.2.2 Factors affecting the mass transport process

1.2.2.2.1 Temperature

1.2.2.2.2 Nature of the polymer

1.2.2.2.3 Nature of the penetrate

1.3 Objective and scope of study

Chapter II Investigation of FRP Chemical Tank

2.1. Introduction

2.2. Background

2.3. Experimental methods

2.3.1 Specimen preparation

2.4 Results & Discussion

2.5 Morphology and Characteristic

2.5.1 SEM/EDS

2.5.1.1 Roof material

2.5.1.2 Upper wall material

2.5.1.3 Lower wall material

2.5.1.4 Bottom

2.6 Conclusion

Chapter III Study of Material Property Under Isothermal Condition and Cyclic Solution

Temperature

3.1 Introduction

3.2 Experimental

3.2.1 Material preparation

3.2.2 Methodology

3.2.2.1 Diffusion of solution under isothermal condition

3.2.2.2 Diffusion of solution under cyclic solution temperature

3.2.3 Measurement of mass uptake

3.2.4 Mechanical property

3.2.5 Morphology and Characterization

3.2.5.1 SEM

3.3 Results & Discussion

3.3.1 Mass uptake

3.3.1.1 Effect of isothermal condition of unsaturated polyester on mass uptake

3.3.1.2 Effect of cyclic solution temperature of unsaturated polyester on mass uptake

3.3.1.2.1 Mass uptake under cyclic solution temperature at 40/80°C

3.3.1.2.2 Mass uptake under cyclic solution temperature at 20/50°C and 20/40°C

3.3.2 Mechanical Property

3.3.2.1 Effect of isothermal condition of unsaturated polyester on mechanical property

3.3.2.2 Effect of cyclic solution temperature of unsaturated polyester on mechanical property at 40/80°C

3.3.2.3 Effect of cyclic solution temperature of unsaturated polyester on mechanical property at 20/50°C and 20/40°C

3.4 Morphology and Characterization

3.4.1 Morphology of material under isothermal condition and cyclic solution temperature

3.4.2 SEM/EDS

3.5 Conclusions

Chapter IV Study of Material Property Under Dynamic Solution Condition

4.1 Introduction

4.2 Methodology

4.2.1 Material preparation

- 4.2.2 Temperature gradient experiment
 - 4.2.3 Cyclic solution concentration experiment
- 4.3 Effect of unsaturated polyester under temperature gradient and concentration gradient in a liquid phase
 - 4.3.1 Mechanical property
- 4.4 Effect of unsaturated polyester under cyclic concentration solution in a liquid phase and vapor phase
 - 4.4.1 Mass uptake
 - 4.4.2 Mechanical property
 - 4.4.3 Color change
 - 4.4.4 Depth of crack
 - 4.4.5 SEM/EDS
- 4.5 Failure Mechanism
- 4.6 Conclusion

Chapter 5 General Conclusion

