

論文 / 著書情報
Article / Book Information

題目(和文)	リチウムをインターカレートした炭素電極の水溶液での電気化学挙動
Title(English)	Lithium-Intercalated Carbon Electrodes and Their Electrochemical Behaviors in Aqueous Solution
著者(和文)	WuYun
Author(English)	Yun Wu
出典(和文)	学位:博士(理学), 学位授与機関:東京工業大学, 報告番号:甲第10426号, 授与年月日:2017年3月26日, 学位の種別:課程博士, 審査員:北村 房男,菅野 了次,川路 均,小泉 武昭,平山 雅章,大坂 武男
Citation(English)	Degree:Doctor (Science), Conferring organization: Tokyo Institute of Technology, Report number:甲第10426号, Conferred date:2017/3/26, Degree Type:Course doctor, Examiner:,,,,,
学位種別(和文)	博士論文
Category(English)	Doctoral Thesis
種別(和文)	論文要旨
Type(English)	Summary

(博士課程)
Doctoral Program

論文要旨

THESIS SUMMARY

専攻 :
Department of Electronic Chemistry 専攻

申請学位 (専攻分 博士
野) : Doctor of (science)

Academic Degree Requested

学生氏名 :
Student's Name Wu Yun

指導教員 (主) :
Academic Advisor(main) Fusao Kitamura

指導教員 (副) :
Academic Advisor(sub)

要旨 (英文 800 語程度)
Thesis Summary (approx.800 English Words)

Lithium-Intercalated Carbon Electrodes and Their Electrochemical Behaviors in Aqueous

Solution (リチウムをインターカレートした炭素電極の水溶液での電気化学挙動)

Chapter 1 General introduction

Graphite intercalation compounds have received much attention because of their unique structures and promising applications for decades. They are formed by the insertion of atomic or molecular layers of a different chemical species called an intercalant accommodated between the graphene layers of graphite which is highly oriented in c-axis and random in a- and b-axes orientation. This structure is of great interest because intercalant species diffuse between graphene layers in the processes of intercalation and deintercalation.

Lithium intercalated graphite exhibits much negative potential close to lithium foil, less reactivity and good reversibility, which became the state-of-the-art anode material of lithium ion battery. And it plays an important role in realizing the lithium “rocking chair” battery because it solved the safety problem of lithium ion battery and commercialized the “rocking chair” system. Consequently, a great number of researches were conducted for this material.

Lithium intercalation into graphite is a staging process, which is characteristic of structure and potential profile. In other words, this staging process is a phase transition process. The kinetics of staging process is closely related to the energy required to overcome the force of Van der Waals between adjacent graphene layers and the repulsive interaction between guest species of lithium.

Lithium could be intercalated into graphene layers of graphite through edge plane and the defect “hole” of basal plane. When lithium is inserted into graphene layers of graphite, the

process is called “intercalation”. When lithium is deinserted from graphene layers of carbon, the process is called “deintercalation”.

The main purpose of this thesis is to study the electrochemical behaviors of lithium-intercalated carbon electrodes in aqueous solution. Two typical kinds of carbon electrodes have been chosen: glassy carbon (GC) with a disordered structure and highly oriented pyrolytic graphite (HOPG) with perfect stacking graphene layers.

Chapter 2 Lithium intercalation into graphene ribbons of glassy carbon

Through XPS, XRD and cyclic voltammetry (CV), it was confirmed that the lithium intercalation into graphene ribbons of the GC electrode substrate during the lithium electrodeposition in PC solution containing 0.1 M LiClO_4 and the lithium deintercalation during the corresponding oxidation process take place. The shift of the (002) Bragg peak to a smaller value of 2θ was observed in the XRD pattern for the lithium – electrodeposited GC powder compared with that for the GC powder. This provided a direct evidence of the lithium intercalation into graphene ribbons of the GC which are stacked in parallel. The formation of Li graphite intercalation compounds, LiC_{6n} , was also confirmed by the XPS measurements. CV was used to characterize the lithium intercalation / deintercalation process. In addition, the results obtained suggested that the lithium insertion / deinsertion to / from the cavities such as microvoids of the GC electrode substrate may occur along with the lithium intercalation / deintercalation.

Chapter 3 Electrochemical behavior of lithium intercalated glassy carbon electrode in aqueous solution

In Chapter 3, the electrochemical behavior of lithium-intercalated glassy carbon (GC-Li) electrode in aqueous solution was investigated. GC-Li electrode showed a potential-independent current in the potential range from -0.2 to 1 V (vs. Ag/AgCl (KCl sat.)). Both anodic and cathodic currents are positive resulting from the oxidation of lithium deintercalated from GC-Li electrode. The whole process would be mainly controlled by lithium diffusion (solid state) from GC-Li electrode substrate to the electrode surface (edge site), the step of lithium oxidation on the electrode surface and the leaving step of lithium ion from its original edge site to solution. The third step was considered to largely affect the whole oxidation process. Consequently, the step of lithium ion leaving from its original edge site is the rate-determining step.

Chapter 4 Lithium intercalated highly oriented pyrolytic graphite and its electrochemical behavior in aqueous solution

In Chapter 4, the lithium electrodeposition was performed at edge plane pyrolytic graphite (EPPG) and basal plane pyrolytic graphite (BPPG) electrodes. The electrochemical behaviors of the two resulting electrodes (EPPG-Li and BPPG-Li) suggested that lithium could be intercalated into graphite structure through edge plane but not basal plane. The perfect structure of EPPG electrode facilitates proposing the model for the electrochemical process of EPPG-Li electrode in aqueous solution. The potential-independent anodic and cathodic currents arise from the oxidation of lithium at the edge site of electrode surface to donate an electron to the external circuit to form lithium ion, and then the resulting lithium ion leaves its original site to aqueous solution to produce a vacant site. There is a chemical potential difference of lithium between the sites occupied with lithium and vacant sites. This chemical potential difference is a driving force for lithium diffusion from the substrate to the vacant site of the electrode surface, resulting in a phase transition in EPPG-Li electrode.

Chapter 5 General conclusions

(1) Lithium could be intercalated / deintercalated into/from GC and EPPG electrodes, but not BPPG electrode.

(2) Lithium-intercalated carbon electrodes (GC and EPPG) show potential-independent positive current in the forward and backward potential scan during the CV measurement for the oxidation. The positive currents result from the oxidation of lithium deintercalated (and deinserted) from lithium-intercalated (and -inserted) carbon electrode.

(3) The electrochemical oxidation is not a usual one-dimensional diffusion-controlled process expected for large planar electrode. The whole oxidation process is mainly controlled by the processes of dissolution of lithium ion and the diffusion of lithium atom in solid state. And the dissolution (solvation) is considered as a rate-determining step.

備考：論文要旨は、和文 2000 字と英文 300 語を 1 部ずつ提出するか、もしくは英文 800 語を 1 部提出してください。

Note: Thesis Summary should be submitted in either a copy of 2000 Japanese Characters and 300 Words (English) or 1 copy of 800 Words (English).

注意：論文要旨は、東工大リサーチリポジトリ(T2R2)にてインターネット公表されますので、公表可能な範囲の内容で作成してください。

Attention: Thesis Summary will be published on Tokyo Tech Research Repository Website (T2R2).

(博士課程)

Doctoral Program

東京工業大学
Tokyo Institute of Technology