

論文 / 著書情報
Article / Book Information

題目(和文)	リチウムイオン導電体Li ₁₀ + δ Ge ₁ + δ P ₂ - δ S ₁₂ 固溶体の合成：導電メカニズム及び全固体電池への応用
Title(English)	Synthesis of a solid solution for the lithium ion conductor, Li ₁₀ + δ Ge ₁ + δ P ₂ - δ S ₁₂ : its conduction mechanism and application to all-solid-state batteries
著者(和文)	Kwon OhMin
Author(English)	Ohmin Kwon
出典(和文)	学位:博士（理学）, 学位授与機関:東京工業大学, 報告番号:甲第9734号, 授与年月日:2015年3月26日, 学位の種別:課程博士, 審査員:菅野 了次,大坂 武男,川路 均,中村 二郎,平山 雅章
Citation(English)	Degree:, Conferring organization: Tokyo Institute of Technology, Report number:甲第9734号, Conferred date:2015/3/26, Degree Type:Course doctor, Examiner:,,,,
学位種別(和文)	博士論文
Category(English)	Doctoral Thesis
種別(和文)	要約
Type(English)	Outline

論文要約

学位申請者氏名	Ohmin Kwon		学籍番号	12D27076
申請学位 (専攻分野)	博士	(理学)	専攻	物質電子化学
論文題目	Synthesis of a solid solution for the lithium ion conductor, $\text{Li}_{10+\delta}\text{Ge}_{1+\delta}\text{P}_{2-\delta}\text{S}_{12}$: its conduction mechanism and application to all-solid-state batteries			

In chapter 1 「Introduction」, this chapter describes background of current research on all-solid-state lithium ion batteries. Well-known lithium superionic conductors and its structure were introduced, and currently proposed interfacial reaction mechanism was explained. Moreover, the purpose and originality of this research was described.

In chapter 2 「Experimental」, synthetic procedure of the $\text{Li}_{10+\delta}\text{Ge}_{1+\delta}\text{P}_{2-\delta}\text{S}_{12}$ (LGPS) and sol-gel solution was described. The measurement condition of X-ray diffraction, neutron diffraction and electrochemical measurement was explained in detail.

In chapter 3 「Synthesis, structure, and conduction mechanism of the lithium superionic conductor $\text{Li}_{10+\delta}\text{Ge}_{1+\delta}\text{P}_{2-\delta}\text{S}_{12}$ 」, this chapter describes existence of solid solution, conduction mechanism in $\text{Li}_{10+\delta}\text{Ge}_{1+\delta}\text{P}_{2-\delta}\text{S}_{12}$ structure.

In chapter 4 「Application of $\text{Li}_{10}\text{GeP}_2\text{S}_{12}$ solid electrolyte to all solid-state batteries with surface-modified LiCoO_2 cathodes」, this chapter describes interface modification and resistive layer formation mechanism between sulfide electrolyte and oxide electrodes to avoid unfavorable interfacial reactions between the oxide electrode and sulfide solid electrolyte, which interrupt all-solid-state battery from practical use.

In chapter 5 「General conclusions」, this chapter describes the summary of this research. A solid solution of $\text{Li}_{10}\text{GeP}_2\text{S}_{12}$ was confirmed, and highly disordered $\text{Li}_{10}\text{GeP}_2\text{S}_{12}$ structure at high temperature was identified by neutron structure analysis. The electrochemical property in all-solid-state batteries was mostly controlled by interfacial reaction between coating layer and sulfide electrolyte.