

論文 / 著書情報
Article / Book Information

題目(和文)	
Title(English)	LES Study of Aerodynamics of Two-dimensional Bluff Bodies in Crossflow at Very High Reynolds Numbers
著者(和文)	曹勇
Author(English)	Yong Cao
出典(和文)	学位:博士(工学), 学位授与機関:東京工業大学, 報告番号:甲第10375号, 授与年月日:2016年12月31日, 学位の種別:課程博士, 審査員:田村 哲郎,喜々津 仁密,山中 浩明,肖 鋒,淺輪 貴史,大風 翼
Citation(English)	Degree;, Conferring organization: Tokyo Institute of Technology, Report number:甲第10375号, Conferred date:2016/12/31, Degree Type:Course doctor, Examiner:,,,,,
学位種別(和文)	博士論文
Category(English)	Doctoral Thesis
種別(和文)	要約
Type(English)	Outline

論文要約

THESIS OUTLINE

専攻 :	環境理工学創造	専攻
Department of		
学生氏名 :	Cao Yong	
Student's Name		

申請学位 (専攻分野) :	博士	(工学)
Academic Degree Requested	Doctor of	
指導教員 (主) :	田村 哲郎	
Academic Advisor(main)		
指導教員 (副) :	喜々津 仁密	
Academic Advisor(sub)		

要約 (様式自由)
Thesis Outline (free format)

LES Study of Aerodynamics of Two-dimensional Bluff Bodies in Crossflow at Very High Reynolds Numbers

There are increasing challenges for the safe and long-lasting structures or structure elements, including the less stiffness of structures and the increasing extreme weather events. The further knowledge of flows past bluff bodies is required to reduce the potential wind damages to such structures as high-rise buildings and bridge cables. Among others, Reynolds number (Re) effects are of great practical significance since the aerodynamic characteristics could be very different varying with Re . Unfortunately the previous studies mostly focused on the subcritical or lower Re s, which are far from those encountered by structures in reality. Considering the feasibility of large-eddy simulation (LES), this thesis aims to clarify the aerodynamics of two-dimensional bluff bodies at very high Re s which are close to the reality of structures. Specifically it includes:

- (1) To explore three-dimensional wake patterns and their effects on aerodynamic forces and pressure on long-span circular cylinders at upper subcritical Re s when vortex-induced vibrations of bridge cables happens in the field observations;
- (2) To investigate supercritical- Re flows around square cylinders with rounded corners which are closer to the reality of high-rise buildings with corner modifications;
- (3) To discover the effects of shear inflow on supercritical flows around a rounded-corner square cylinder, as an example of external effects.

The outline of the thesis is shown in the following schematic. Firstly the numerical methods are validated systematically in Chapter 3 based on unstructured-grid LES and structured-grid LES for predicting unsteady flows around a square cylinder at the high subcritical Re s. In particular, the numerical schemes for convective terms, meshing strategies and spanwise lengths are examined for the unstructured-grid LES. On the whole, LES based on both grid systems are able to provide fairly accurate prediction of time-averaged and r.m.s quantities. The appropriate numerical schemes and meshing strategies are suggested for simulations of subcritical flows. Moreover, the spanwise length plays an important role in obtaining reasonable spanwise correlation of pressure and consequently the overall fluctuating lifts. Unstructured grids will be used in Chapter 4 for the subcritical flows past a circular cylinder with strongly vigorous vortex shedding, while structured grids will be applied in Chapter 5 & 6 for

Following that, the aerodynamics of circular cylinders at upper subcritical Re is studied in Chapter 4, with a focus on three-dimensional vortex shedding. It was found that even at such high Re , a three-dimensional pattern of vortical field is also present in the wake with a large phase lag in primary vortex shedding. The development process of three-dimensional wakes starts from local phase variations in primary vortex shedding, which are induced by the “irregular” streamwise vortex. The followed wake is associated with a successive evolution composed of certain stages in order, e.g., oblique vortex shedding. Moreover, such three-dimensional patterns also weakens vortex shedding in cross sections perpendicular to the axis of the cylinder, leading to modulations of sectional lift coefficients.

To summarize, the findings and the systematical explanations about the very-high-Re flows around the typical bluff bodies will benefit greatly the understandings of wind forces acting on structures in architectural and civil engineering.

