

論文 / 著書情報
Article / Book Information

Title	Traffic state estimation on highway: A comprehensive survey
Authors	Seo, T., Bayen, A. M., Kusakabe, T., Asakura, Y.
Citation	Annual Reviews in Control, Vol. 43, , pp. 128-151
Pub. date	2017, 4
DOI	http://dx.doi.org/10.1016/j.arcontrol.2017.03.005
Creative Commons	See next page.
Note	This file is author (final) version.

License



Creative Commons: CC BY-NC-ND

Traffic state estimation on highway: A comprehensive survey

Toru Seo^{a,*}, Alexandre M. Bayen^b, Takahiko Kusakabe^c, Yasuo Asakura^a

^aTokyo Institute of Technology, 2-12-1-M1-20, O-okayama, Meguro, Tokyo 152-8552, Japan

^bUniversity of California, Berkeley, 109 McLaughlin Hall, Berkeley CA 94720-1720, United States

^cCenter for Spatial Information Science, the University of Tokyo, 5-1-5 Kashiwanoha, Kashiwa-shi, Chiba 277-8568, Japan

Abstract

Traffic state estimation (TSE) refers to the process of the inference of traffic state variables (i.e., flow, density, speed and other equivalent variables) on road segments using partially observed traffic data. It is a key component of traffic control and operations, because traffic variables are measured not everywhere due to technological and financial limitations, and their measurement is noisy. Therefore, numerous studies have proposed TSE methods relying on various approaches, traffic flow models, and input data. In this review article, we conduct a survey of highway TSE methods, a topic which has gained great attention in the recent decades.

We characterize existing TSE methods based on three fundamental elements: estimation approach, traffic flow model, and input data. Estimation approach encompasses methods that estimate the traffic state, based on partial observation and a priori knowledge (assumptions) on traffic dynamics. Estimation approaches can be roughly classified into three according to their dependency on a priori knowledge and empirical data: model-driven, data-driven, and streaming-data-driven. A traffic flow model usually means a physics-based mathematical model representing traffic dynamics, with various solution methods. Input data can be characterized by using three different properties: collection method (stationary or mobile), data representation (disaggregated or aggregated), and temporal condition (real-time or historical).

Based on our proposed characterization, we present the current state of TSE research and proposed future research directions. Some of the findings of this article are summarized as follows. We present model-driven approaches commonly used. We summarize the recent usage of detailed disaggregated mobile data for the purpose of TSE. The use of these models and data will raise a challenging problem due to the fact that conventional macroscopic models are not always consistent with detailed disaggregated data. Therefore, we show two possibilities in order to solve this problem: improvement of theoretical models, and the use of data-driven or streaming-data-driven approaches, which recent studies have begun to consider. Another open problem is explicit consideration of traffic demand and route-choice in a large-scale network; for this problem, emerging data sources and machine learning would be useful.

Keywords: highway operation, traffic state estimation, traffic flow model, numerical scheme, traffic data

1. Introduction

Traffic state estimation (TSE) refers to the process of inference of traffic state variables, namely flow (veh/h), density (veh/km), speed (km/h), and other equivalent variables, on road segments, using partially observed and noisy

*Corresponding author

Email addresses: t.seo@plan.cv.titech.ac.jp (Toru Seo), bayen@berkeley.edu (Alexandre M. Bayen), t.kusakabe@csis.u-tokyo.ac.jp (Takahiko Kusakabe), asakura@plan.cv.titech.ac.jp (Yasuo Asakura)

Frequently used abbreviations: ADAS: advanced driver assistance system, ARZ: Aw-Rascle-Zhang, ASF: adaptive smoothing filter, BVP: boundary value problem, CDR: call detail record, CL: conservation law, CTM: cell transmission model, EKF: extended Kalman filter, EnKF: ensemble Kalman filter, FD: fundamental diagram, FDM: finite difference method, GPS: global positioning system (and equivalent global navigation satellite systems), HJ: Hamilton-Jacobi, HL: Hopf-Lax, KF: Kalman filter, KFT: Kalman filter-like technique, LWR: Lighthill-Whitham-Richards, ML: machine learning, OBD2: on board diagnostics second generation, PDE: partial differential equation, PF: particle filter, PTM: phase transition model, PW: Payne-Whitham, SMM: switching mode model, TSE: traffic state estimation, TTI: travel time information, VT: variational theory, xFCD: extended floating car data,




Figure 1: Illustration of TSE, where entire traffic state (plot color: density) in the time–space domain is reconstructed based on partial observation by stationary (density at specific locations) and mobile (subsets of trajectories of specific vehicles) sensing data. The data is based on [US Department of Transportation \(2006\)](#).

traffic data. TSE plays an important role in traffic operations and planning. For example, traffic control, such as ramp metering, pricing, and information provision, requires precise traffic state information in order to mitigate congestion effectively. Strategic transportation planning such as infrastructure improvements also require traffic state information. These operation and planning tasks can be greatly improved by an efficient and accurate observation of the traffic state. However, the traffic state is not observed everywhere and practical measurements are usually noisy. Thus, the traffic state in unobserved areas needs to be estimated; and that in observed areas needs to be improved (denoised) as well. In this article, TSE is defined as the *simultaneous estimation of flow, density, and speed on road segments with high spatiotemporal resolution*,¹ based on partially observed traffic data and a priori knowledge of traffic. Fig. 1 illustrates a conceptual procedure of TSE.

This article focuses on TSE on highways motivated by the following four reasons. First, highways play a significant role in road transportation systems, with high service capability in terms of the volume and speed. Second, they exhibit some controllability ([Papageorgiou et al., 2003](#)) because of the nature of vehicular traffic. Third, recent technology developments enable new applications with the use of various and heterogeneous traffic data. Fourth, because of the aforementioned reasons, numerous highway TSE methods with various features have been proposed to date, which are worth considering and summarizing.

For our best knowledge, there is no comprehensive survey on TSE, although more than a decade has passed from the early and influential work on highway TSE by [Wang and Papageorgiou \(2005\)](#) and there have been considerable advances in this field.² This makes it difficult to assess available approaches, respective benefits, and potential improvements.

The aims of this article are to provide a comprehensive and systematic summary of highway TSE, to contribute toward a better understanding of state-of-the-art methods, and to identify future research directions. Note that this article does not determine which methodology outperforms others in terms of general performance metrics. Respective advantages or disadvantages of a TSE method need to be discussed separately, by considering the specification of the application. One of the aims of this article is to provide the fundamental materials for such discussion. To achieve these aims, this article characterizes existing TSE methods based on their three fundamental elements: *estimation approaches*, *traffic flow models*, and *input data*. The following briefly describes these elements (we will discuss the details in the corresponding sections later).

¹“High spatiotemporal resolution” loosely means spatial discretization on the order of few hundreds meters, and temporal on the order of a few minutes for practical purposes in transportation engineering.

²Several review articles from specific perspectives have been provided: a comprehensive review in 2005 ([Wang and Papageorgiou, 2005](#), section 1) (we avoid overlapping with this one), data fusion in generic intelligent transportation system (ITS) research ([El Faouzi et al., 2011](#)), emerging traffic data collection methods in 2011 ([Antonioni et al., 2011](#)), coordinate system in traffic flow models for TSE ([Yuan, 2013](#), chapter 2), TSE for specific ITS applications ([Timotheou et al., 2015b](#), section 3), and application of vehicular ad hoc networks ([Song and Lee, 2013](#); [Darwish and Abu Bakar, 2015](#)).

The estimation approach consists of methods that estimate the traffic state, based on a priori knowledge of traffic and partial observation. A priori knowledge (i.e., assumptions) could be physical traffic flow models and data-driven models, which is usually obtained by abstracting actual traffic by employing physical principles and statistical/machine-learning (ML) methods, respectively. In this study, the approaches are grouped into three categories, namely, *model-driven*, *data-driven*, and *streaming-data-driven*, according to types of a priori knowledge and input data they rely on. In short, model-driven ones rely on physical models of traffic which is characterized by empirical relation. Data-driven ones rely on dependence in historical-data and statistical/ML methods. Streaming-data-driven ones do not rely on these two previous elements. Because the assumptions vary greatly among the approaches, they have different advantages and disadvantages.

Traffic flow models describe the physical and theoretical aspects of traffic dynamics in the spatiotemporal domain. Therefore, they are used by model-driven TSE methods to infer the traffic state in an unobserved time-space region. Various models along with various solution methods have been proposed; and they have totally different advantages and disadvantages in terms of TSE.

The input data for TSE is the partial observation of traffic and is essential for TSE. Because of recent technology advances, the availability of novel data types (e.g., global positioning system (GPS), call detail record (CDR), on board diagnostics second generation (OBD2), etc.) is rapidly increasing in terms of both quality and quantity. This has resulted in the emergence of various TSE methods.

The remainder of this article is organized as follows. In Section 2, we briefly present highway traffic and TSE, along with fundamental terms and definitions. In Section 3, we summarize existing traffic models commonly used for TSE. In Section 4, we describe available measurements and data for traffic. In each sub- and sub-sub-section in Sections 3 and 4, general introduction on the corresponding topic and its application in TSE are discussed sequentially. In Section 5, we review TSE approaches, which mainly use models described in Section 3 and data described in Section 4. In Section 6, we summarize the survey results and propose future research directions.

Note that there are over 100 different methods to the TSE problem; thus, it is not practical to enumerate and explain them all in the core of this article. Therefore, only studies with substantial originality in terms of the aforementioned characteristics (i.e., approach, model, data) are referred in the main text. The remaining studies are summarized in Tables 1–4 together with those explained in the main text. Case studies which did not propose new TSE methods are not reviewed in this article.

2. Highway traffic and state estimation

In this section, we provide preliminary information about highway traffic and basic introduction of TSE. For systematic introduction to state-of-art of traffic flow and its theory, see, for example, [Treiber and Kesting \(2013\)](#) and [Garavello et al. \(2016\)](#).

2.1. Link

First, traffic on a link is considered. A link is defined as a road segment without an internal merge/diverge section, and is directional in the case of a highway.

At a microscopic scale, traffic on a link can be represented as a set of *vehicle trajectories*. A vehicle trajectory can be represented as $X(t, n)$ and $L(t, n)$, a position and lane-index, respectively, of vehicle n at time t . The position is often defined as the distance along the road from its origin (i.e., postmile). Fig. 2d shows examples of vehicle trajectories in a freeway ([US Department of Transportation, 2006](#)) (sampling ratio: 1/33).

At a macroscopic scale, traffic on a link is often represented by a *traffic state*, which can be a subset of the following variables: *flow* q , *density* ρ , and *average speed* v .³ The flow, also known as the flow-rate or volume by practitioners, is the number of vehicles that pass a given point per unit time; the density is the number of vehicles per unit space; and the average speed (or simply, speed) is the mean of the instantaneous speeds among vehicles. [Edie \(1963\)](#) proposed a generalized definition of traffic states. A traffic state in a time-space region \mathbf{A} was defined by Edie as follows:

³Technically, a set of two variables from among flow or headway, density or spacing, and speed or pace ([Laval and Leclercq, 2013](#)) is a sufficient definition for a traffic state, since $q = \rho v$ holds.

$$q(\mathbf{A}) = \frac{d(\mathbf{A})}{|\mathbf{A}|}, \quad (1)$$

$$\rho(\mathbf{A}) = \frac{t(\mathbf{A})}{|\mathbf{A}|}, \quad (2)$$

$$v(\mathbf{A}) = \frac{d(\mathbf{A})}{t(\mathbf{A})}, \quad (3)$$

where $d(\mathbf{A})$ is the total distance traveled by all the vehicles in the region \mathbf{A} (veh km), $t(\mathbf{A})$ is the total time spent by all the vehicles in region \mathbf{A} (veh h), and $|\mathbf{A}|$ is the time–space area of the region \mathbf{A} (km h). For practical scenarios, specific definitions are often used, such as point flow in space, space density, and space mean speed at a time point. The definition can be applied to either a single lane or multiple lanes in a link. Figs. 2a–2c show examples of traffic state variables, corresponding to the trajectories of Fig. 2d. The definition of q , ρ , v and the way they relate to particles (i.e., individual vehicles) are historically inspired by hydrodynamics.

Cumulative flow (also known as accumulated vehicle count, cumulative surface, Moskowitz function, etc.) is a unified representation of traffic where lane-changing is ignored. Cumulative flow $N(t, x)$ is defined as the number of vehicles that passed position x by time t . Continuous cumulative flow shapes a continuous “surface” in the vehicle–time–space (n – t – x) domain, in which information about all the aforementioned traffic states are included (Moskowitz, 1965; Makigami et al., 1971). For example, a contour line of a cumulative surface, where the n -axis is the height, is a vehicle trajectory $X(t, n)$ if there is no lane-changing. In addition, partial derivatives of N represent the traffic state at the corresponding time–space point:

$$q(t, x) = \partial_t N(t, x), \quad (4)$$

$$\rho(t, x) = -\partial_x N(t, x), \quad (5)$$

$$v(t, x) = \frac{q(t, x)}{\rho(t, x)}. \quad (6)$$

By taking limit of Eqs. (1) and (2) as size of \mathbf{A} to be zero, they lead Eqs. (4) and (5). Fig. 2e shows an example of a cumulative flow for freeway data (contour interval: 33). Note that it slightly differs from Fig. 2d, as heterogeneity among lanes is averaged.

Fig. 2 shows an example of traffic state, vehicle trajectories, and cumulative flow in time–space diagrams based on the same traffic in NGSIM dataset (US Department of Transportation, 2006). Specific to this data, congestion (high density and low speed) was observed around $t = 200, 300$, and 700 (s) at $x = 600$ (m) and propagates spatially backwards as time progresses.

2.2. Network

A network is a set of links and nodes, in which the links are connected by the nodes. At a node, traffic may merge and/or diverge. Additionally, there are source and sink nodes (i.e., boundaries) where traffic demand is generated and attracted (except for a closed loop network, which is not practical). Fig. 3 illustrates the relation between links and nodes.

In a highway network, merge/diverge nodes correspond to junctions between multiple highway routes, and source/sink nodes correspond to on/off-ramps from/to arterial roads or boundaries of the spatial area of interest. At a diverge node, a driver of a vehicle has to determine which route s/he uses. At a source node, a driver has to determine when s/he enters the mainline. At a sink node, a driver has to determine whether s/he exits from the network. All these choices depend on her/his preferences, the travel itinerary, and traffic situation, which are not necessarily observable.

2.3. Traffic state estimation

2.3.1. Overview

In this article, TSE methods are characterized according to three elements: estimation approach, traffic flow model, and input data. The conceptual relation among these elements is shown in Fig. 4.




Figure 2: Time–space diagram of traffic state, vehicle trajectories, and cumulative flow. The data is based on [US Department of Transportation \(2006\)](#).




Figure 3: Sample road network.

Estimation approaches are grouped into three categories, namely, *model-driven*, *data-driven*, and *streaming-data-driven*, depending on assumptions (i.e., models) and input data. Missing/noisy data imputation like TSE always requires exogenous assumptions. Such assumptions can be “strong” or “weak” in a relative context. An assumption is “stronger” if it cannot be justified without extensive empirical validation. Examples of “strong” assumptions are traffic flow models which are developed based on empirical observation, and values of the model parameters which are subject of empirical calibration. A “strong” assumption is highly useful to estimate traffic state accurately, if the assumption is valid. On the other hand, excessive error will be caused if the assumption becomes invalid (e.g., a standard traffic flow model in a presence of a traffic accident). The problem is that, in general, it is not always possible to determine whether the assumption is valid or not under the practical TSE situation. It means that a TSE method with “strong” assumption can be vulnerable against unpredictable or uncertain traffic phenomena. Therefore, in general, it would be practically preferable if accurate TSE is possible based on “weaker” assumptions. In this article, traffic flow models with empirical relation and use of (statistical) dependency in historical-data are considered as “strong”




Figure 4: Traffic state estimation with assumptions and inputs.

assumptions.⁴

The model-driven approach are defined as an approach for TSE that uses a physical model describing traffic dynamics, namely, a traffic flow model. They estimate traffic states in unobserved areas using the model, and real-time data as its input. The models are usually based on empirical relation; the parameters describing the relation are either exogenously calibrated by using historical-data or endogenously estimated within the methods. The model-driven approaches have been widely used by existing TSE methods.

The data-driven approach are defined as an approach for TSE that extensively relies on *historical-data*, instead of physical traffic flow models. The approach extracts dependence between data from historical-data by using statistical/ML methods, and then estimates the traffic state based on real-time data and the dependence. This means that it does not require a priori knowledge of traffic being modeled explicitly as in physical traffic flow models. The approach generally requires large amount of historical-data.

The streaming-data-driven approach are defined as an approach for TSE that uses real-time (i.e., streaming) data only and is not strongly characterized by empirical relation which can be found in common traffic flow models (e.g., the fundamental diagram). It means that the approach less relies on a priori knowledge on traffic compared to the other two approaches (i.e., it only uses “weaker” assumptions). On the other hand, it may requires large amount of streaming data, and its accuracy may not be as high as that of model-driven or data-driven approaches if traffic was predictable.

Traffic flow models have been used by model-driven TSE methods as mentioned earlier. They describe traffic dynamics, such as propagation of congestion, mainly according to some physical principles and empirical relation. Various traffic flow models have been proposed to date and formulated under different assumptions. Various numerical

⁴A typical example of “strong” assumption is the existence of the fundamental diagram (FD) (c.f., Sections 3.1 and 3.2) of traffic, which consists of a functional form and parameter value of the FD. It is often assumed that functional form and parameter value of the FD are constant. If these assumption are valid, traffic dynamics can be well reproduced and accurate TSE is possible. In other words, accuracy of a TSE method with “strong” assumption may be high under ordinary traffic conditions. However, the parameter values can be changed by uncertain or unpredictable events such as so-called capacity drop and traffic accidents. Under such situations, accuracy of a TSE method with the constant FD (i.e., “strong” assumption) will be lower than a method with variable FD or without FDs (i.e., methods with “weaker” assumption). Therefore, the overall performance of a TSE method with “strong” assumptions is not necessarily better than that with “weak” assumptions; it depends on actual traffic situations.

Contrary, a typical example of “weak” assumptions is the conservation law of vehicles, which essentially means vehicles do not appear nor disappear without good reasons.




Figure 5: Traffic data and its spatiotemporal relation.

schemes to compute theoretical models have been proposed as well, and each scheme has unique advantages and disadvantages in terms of TSE.

Data is essential for all TSE methods. It is used as real-time data and/or historical-data by a TSE method. The real-time data is data collected at the moment when the unobserved traffic state is estimated, and is utilized for all TSE. The historical-data is data collected at the past for a long term, and is often used for model calibration or identification in model-driven and data-driven TSE. Fig. 5 shows the conceptual relation between TSE, real-time data, and historical-data. Because of recent advances in information and communication technology (ICT), a wide variety of data is available at the present time. Data types are grouped into two categories according to the measurement methodology: stationary and mobile. Stationary data is collected by fixed sensors, such as inductive loops, and can be considered as conventional. Mobile data is collected by mobile sensors, such as on-vehicle GPS devices, and is relatively new. With the emergence of connected and automated vehicles, this kind of data is becoming an increasing source of traffic data. Additionally, we introduce another independent categorization: aggregated and disaggregated. In aggregated data, information from multiple vehicles is aggregated (e.g., 5 min time interval) and stored. In disaggregated data, it is not aggregated and is stored as collected; therefore, it contains more information than the aggregated data, and may require advanced techniques to be used. Various techniques have been developed to use this data.

In the following sections, traffic flow models are first discussed in Section 3. Then, data is discussed in Section 4, as the use of specific data requires some knowledge about the models. Finally, approaches are discussed in Section 5, because they integrate models and data to estimate the traffic state.

2.3.2. Application

TSE methods are generally applied to traffic operations. The most notable application is traffic control mainly to mitigate traffic congestion. Examples of control on the highway are ramp metering, variable speed limit, pricing, and information provision for route choice guidance. Each of these requires precise information about traffic states (Papageorgiou et al., 2003). Results of TSE can be also used for strategic planning, such as road construction.

3. Traffic flow models

In this section, we introduce the different frameworks used for traffic flow models and review their applications to TSE. Each section describes general introduction on each topic first, and then reviews its application to TSE. In




Figure 6: Flow–density relation in actual traffic data. Each dot represent a traffic state in a $2\text{sec} \times 50\text{m}$ -sized domain in dataset of [US Department of Transportation \(2006\)](#).

Section 3.1, we explain a fundamental concept in traffic flow theory: the *fundamental diagram (FD)*. In Section 3.2, we present the models that describe traffic in a link, and then in Section 3.3, we briefly describe the models for nodes.

3.1. Fundamental diagram

The FD, also known as a speed–density relation, flow–density relation, or flux function, is one of the most fundamental concepts in traffic flow theory. It describes the empirical relation among traffic state variables in *stationary* traffic (also referred as *steady* or *equilibrium* traffic), which is an ideal state in which all vehicles have the same constant speed and spacing. The FD appears in almost all theories of traffic flow as it relates the traffic state variables and contains remarkable information about traffic characteristics, such as free-flow speed and capacity ([Greenshields, 1935](#)) and is inherently linked to flux functions in hydrodynamic theory ([Lamb, 1932](#); [Evans, 1998](#)). Fig. 6 shows a flow–density relation in actual traffic. The typical FD theory assumes that the traffic state (q, ρ, v) in stationary traffic satisfies

$$v = V(\rho), \quad (7)$$

or equivalently,

$$q = \rho V(\rho) = Q(\rho), \quad (8)$$

where V represents the speed–density FD and Q represents the flow–density FD. The FD has two essential elements: functional form and parameters values. The elements depend on various factors, such as spatial conditions (e.g., road geometric alignment and road surface), temporal conditions (e.g., time of day, weather, accident), and vehicle conditions (e.g., hardware performance and driver characteristics).

Various functional forms for FDs have been proposed. A triangular FD ([Newell, 1993a](#)) is one of the most popular forms because of its simplicity, theoretically preferable features (c.f., Section 3.2), and some empirical evidence ([Cassidy, 1998](#)). Fig. 7 shows examples of a triangular FD in various planes: the blue curves represent free-flowing regimes and red curves represent congested regimes. Other forms have been proposed and used as well, including differentiable, noncontinuous, or multivalued forms. For the details, see recent reviews by [Traffic Flow Theory and Characteristics Committee \(2011\)](#); [Carey and Bowers \(2012\)](#); [van Wageningen-Kessels et al. \(2014\)](#).

In fact, traffic characteristics may vary depending on time, vehicle, and location. This is called traffic heterogeneity. Therefore, technically, the FD function can be expressed as $Q(\rho, t, n, x)$. For example, lane-drops can be represented by a space(x)-varying FD. Difference between passenger vehicles and heavy trucks can be represented by a vehicle(n)-varying FD. Weather change can be represented by a time(t)-varying FD. Capacity drop at sags is known to be affected by spatial and driver conditions; therefore, it can be represented by a vehicle-space(n, x)-varying FD. However, depending on importance of heterogeneity to the application, some of the dependencies are simplified or neglected to enable efficient calibration and estimation.




Figure 7: Triangular FD.

Identifying the values of the FD parameters has attracted a significant amount of interests over the past decades. Most existing calibration methods are based on stationary sensors (e.g., [Dervisoglu et al., 2009](#); [Chiabaut et al., 2009](#); [Coifman, 2014](#); [Zhong et al., 2015](#)), and some studies have considered mobile data, such as the GPS probe vehicles with some assumptions ([Herrera et al., 2010](#); [Seo et al., 2016a](#)) and probe vehicles with additional sensors ([Seo et al., 2015b](#)).

Application to TSE: Because the FD relates traffic state variables to each other and is a core of traffic flow theory, it plays a significant role in most of TSE methods. If a TSE method requires an FD, its functional form is given considering its requirement and a priori knowledge of the fitness to empirical data. Then, its parameters are either calibrated based on a priori knowledge/data (i.e., offline calibration) or jointly estimated with the traffic state (i.e., online calibration, adaptive estimation). The former makes the problem simple and easily solved; therefore, many studies used this approach. However, such methods can be disrupted if the FD changes dynamically. The latter is robust against such phenomena. For example, [Wang et al. \(2009\)](#) performed adaptive TSE by considering the time and space dependencies of an FD (i.e., $V(\rho, t, x)$) to capture the effect of traffic accidents.

Conversely, some of the data-driven methods and streaming-data-driven methods do not rely on FDs at all (e.g., [Chen et al., 2003](#); [Coifman, 2003](#); [Seo et al., 2015a](#); [Bekiaris-Liberis et al., 2016](#)); thus, they require least a priori knowledge. This means that they can be robust against uncertain phenomena and unpredictable incidents, and require less—or no—calibration.

3.2. Link models

Traditionally, traffic on a link is modeled using partial differential equation(s) (PDE) representing a system of *conservation law (CL)* in hydrodynamic flow modeling, which describes aggregated behavior of traffic by approximating it as continuum fluid (and its discretization). The model uses the concept of the FD (c.f., Section 3.1) as a basis of its flux functions. Because of its continuum fluid approximation, the model is often called a macroscopic




Figure 8: Traffic flow, its PDE model, and discretized numerical scheme.

model.⁵ Fig. 8 shows a conceptual example of traffic flow, its continuous PDE model, and discretized numerical scheme.

In Section 3.2.1, we introduce typical (seminal) traffic flow models. In Section 3.2.2, we briefly describe the extension of the basic models. In Section 3.2.3, we explain the solution methods (i.e., numerical schemes) for the models.

3.2.1. One-dimensional flow models

The Lighthill–Whitham–Richards (LWR) model (Lighthill and Whitham, 1955; Richards, 1956), also known as a first-order model, is the most seminal work in macroscopic traffic flow modeling. The LWR model assumes a CL and that the traffic state is always equilibrated following an FD. It can be formulated as

$$\partial_t \rho + \partial_x(\rho v) = 0, \quad (9a)$$

$$v = V(\rho), \quad (9b)$$

or equivalently,

$$\partial_t \rho + \partial_x Q(\rho) = 0. \quad (10)$$

⁵There are other models, such as microscopic models (e.g., car-following models and cellular automata), mesoscopic models (e.g., gas-kinetic models), and others (Helbing, 2001; Hoogendoorn and Bovy, 2001). However, they have not been used for TSE in the past because of their complexity and high computational cost, with some exceptions that are, in fact, equivalent to macroscopic models.

Eq. (9a) represents a CL and Eq. (9b) represents the FD. The model can reproduce basic phenomena of traffic, such as a distinction between a free-flowing regime and congested regime, and simple behavior of a traffic jam and shockwave. Additionally, the model can be calibrated and solved efficiently because of its simplicity. However, several limitations have been pointed out. The equilibrium assumption (9b) means that only traffic states following the FD are allowed to exist. In addition, this model makes vehicles change their speed instantaneously; obviously, this is a crude approximation of vehicle dynamics. These limitations and the mathematical features of this model make it impossible for the model to reproduce well-known phenomena, such as the capacity drop, hysteresis effect, traffic instability, stop-and-go waves, etc.

Higher-order models have been developed to overcome the limitation of the LWR model. To represent shifts (also referred as perturbation, non-equilibrium state) from the equilibrium traffic state, these models generally use an additional equation (referred as the momentum equation) that describes the dynamics of v , instead of the FD equation (9b) in the LWR model. The Payne–Whitham (PW) model (Payne, 1971; Whitham, 1974) is the first well-known attempt at higher-order modeling. It can be formulated as

$$\partial_t \rho + \partial_x(\rho v) = 0, \quad (11a)$$

$$\partial_t v + v \partial_x v = -\frac{v - V(\rho)}{\tau} - \frac{c_0^2}{\rho} \partial_x \rho, \quad (11b)$$

where τ is the relaxation time and c_0^2 is a parameter related to driver anticipation. Eq. (11b) is the momentum equation. The PW model and its extensions (e.g., Papageorgiou et al., 1989) succeed in reproducing complex traffic phenomena to some extent. However, it may produce physically inappropriate behavior, such as negative speed and information propagating faster-than-vehicle speed (for the details, see the discussion by Del Castillo et al. (1994); Daganzo (1995); Papageorgiou (1998); Hoogendoorn and Bovy (2001)).

The Aw–Rascle–Zhang (ARZ) model (Aw and Rascle, 2000; Zhang, 2002) is another well-known higher-order model. It allows traffic states to shift from the equilibrium, and it overcomes the aforementioned limitation of the PW model. It can be formulated as

$$\partial_t \rho + \partial_x(\rho v) = 0, \quad (12a)$$

$$\partial_t(v - V(\rho)) + v \partial_x(v - V(\rho)) = -\frac{v - V(\rho)}{\tau}. \quad (12b)$$

Eq. (12b) is the momentum equation. The ARZ model converges to the LWR model at $\tau \rightarrow 0$; therefore, it can be regarded as a generalization of the LWR model (in the physical sense). Further generalization and extension of the ARZ model have been proposed, such as generic second order models (Lebacque et al., 2007), phase transition models (PTM) (Colombo, 2003; Blandin et al., 2011), and the generalized ARZ model (Fan et al., 2014).

Recently, there have been theoretical advances in the interpretation of traffic flow models. That is, the connection between the some of the models and the Hamilton–Jacobi (HJ) PDE, which is well studied in PDE and physics communities (Evans, 1998). For example, the conventional LWR model (10), in which the state variable is $\rho(t, x)$, can be transformed into following equation where the state variable is the cumulative flow, $N(t, x)$ (Newell, 1993a,b,c):

$$\partial_t N - Q(-\partial_x N) = 0. \quad (13)$$

This equation is an HJ PDE whose Hamiltonian is the FD.⁶ Therefore, for example, the model can be efficiently solved by using techniques in HJ PDE theory (Aubin et al., 2008; Claudel and Bayen, 2010a,b). In addition, because of the nature of the cumulative flow (c.f., Section 2.1), the model can describe vehicle trajectories and travel time explicitly. It shows an essential connection between the macroscopic traffic flow model and microscopic vehicle behavior (e.g., car-following model); this can be considered as a preferable feature for a physical model. This is also a preferable feature to exploit mobile data (i.e., trajectories of probe vehicles) in a straightforward manner (for the details, see Section 4.2). Based on this theory, new coordinate system called *Lagrangian* coordinates⁷ (the conventional is *Eulerian* coordinate

⁶For the proper mathematical link to HJ and viability framework for Eq. (13), see Aubin et al. (2008); Claudel and Bayen (2010a,b).

system based on (t, x)) is proposed to use the cumulative flow and vehicle trajectories in macroscopic traffic flow model (e.g., [Newell, 2002](#); [Daganzo, 2006](#); [Leclercq et al., 2007](#); [Laval and Leclercq, 2013](#)). Similar topics for other traffic flow models have also been discussed ([Aw et al., 2002](#); [Jin, 2016](#)).

Application to TSE: The aforementioned models have been extensively applied for model-driven TSE. The LWR model is the most widely applied (e.g., [Haj-Salem and Lebacque, 2002](#); [Muñoz et al., 2003](#)). One of the reasons for this is that the model can be calibrated and solved efficiently. Another reason is that the model can explicitly manage vehicle trajectory data, which has received a great deal of attention recently (e.g., [Claudel and Bayen, 2008](#)); in fact, this feature is also because of the model’s simplicity (c.f., Sections 3.2.3, 4.2). Some studies have used part of the LWR model’s implications (i.e., propagation speed of a shockwave) for TSE (e.g., [Coifman, 2002](#); [Treiber and Helbing, 2002](#)). Regarding the HJ PDE version of the LWR model, some recent studies have applied the theory of HJ PDE or the Lagrangian coordinate system (e.g., [Coifman, 2002](#); [Claudel and Bayen, 2008](#); [Yuan et al., 2012](#)) in order to utilize disaggregate vehicle trajectory data. Besides, higher-order models are used in TSE studies to estimate the non-equilibrium traffic state and/or acceleration rates, which are significantly important for some traffic operations and ignored by the LWR model. For example, the PW model and its extension (e.g., [Nanthawichit et al., 2003](#); [Wang et al., 2006](#)), higher-order model modified from the LWR model (e.g., [Mihaylova and Boel, 2004](#)), ARZ model and its extension (e.g., [Wilkie et al., 2013](#); [Fan et al., 2014](#)), and several PTMs (e.g., [Blandin et al., 2013](#); [Piccoli et al., 2013](#)) have been used.

3.2.2. Extensions

Several extensions of one-dimensional models have been proposed. In this section, we describe multi-lane, multi-class, and stochastic modeling.

Actual traffic is often multi-lane and multi-class; however, the models described in Section 3.2.1 are based on single-lane and single-class. To account for this problem, some link models that explicitly consider multi-lane and/or multi-class behavior of traffic have been developed. These extensions are quite advanced and technical topics; therefore, refer, for example, to [Wong and Wong \(2002\)](#), [Daganzo \(2002\)](#), [Laval and Daganzo \(2006\)](#), [van Wageningen-Kessels et al. \(2014\)](#), and [Costeseque and Duret \(2016\)](#) and references therein for the case of the LWR model. One of the main challenges for such extensions is modeling lane-changing behavior, in which human behavior is essentially important. Nevertheless, it should be noted that the ARZ model and its extension can be considered as a multi-class LWR model because it can be interpreted as the LWR model with vehicle-specific FDs.

Another important aspect of traffic flow modeling is the stochastic factors. Stochastic models have been developed to explain the uncertainty of traffic dynamics and effect of the input data’s uncertainty on the model’s output. For example, [Sumalee et al. \(2011\)](#) developed a stochastic model based on the LWR model that considered both factors. In models of [Jabari and Liu \(2012\)](#) and [Jabari et al. \(2014\)](#), the source of stochasticity in traffic dynamics accounted for vehicle heterogeneity, which implied a relation between multi-class and stochastic models. [Wada et al. \(2017\)](#) developed a stochastic model based on the HJ PDE version of the LWR model.

Application to TSE: Some studies have investigated multi-class and/or multi-lane TSE. For example, [van Lint et al. \(2008\)](#); [Ngoduy \(2008\)](#) proposed multi-class TSE methods, Chapter 4 of [Yuan \(2013\)](#) proposed a multi-class TSE method in Lagrangian coordinates, and [Lovisari et al. \(2015\)](#) developed a multi-lane TSE method. [Coifman \(2003\)](#) proposed a multi-lane TSE method that is not model-driven. Note that single-class single-lane TSE models are not necessarily impractical in multi-class multi-lane environments; because their results can be interpreted as an “average state” of multi-class multi-lane traffic ([Papageorgiou, 1998](#)). However, for the case of mobile data (c.f., Section 4.2), ignoring multi-class behavior can cause a biased estimation because data might be sampled from biased classes. Additionally, rich disaggregated data (c.f., Section 4.2) is possibly problematic for single-class single-lane models because of, paradoxically, its richness ([Seo and Kusakabe, 2015](#)). For example, if a probe vehicle overtakes another, a singularity will arise in the single-lane Lagrangian coordinate.⁸ To the best of the authors’ knowledge, no studies have solved this problem explicitly.

Several TSE studies have used stochastic models to capture estimation uncertainty explicitly. For example, [Sumalee et al. \(2011\)](#), [Laval et al. \(2012\)](#), and [Jabari and Liu \(2013\)](#) proposed TSE methods based on their stochastic

⁷e.g., other HJ PDEs such as $\partial_t X(t, n) - V(-\partial_n X(t, n)) = 0$ which is equivalent to Eq. (13). Notice that $X(t, n)$ is a trajectory of vehicle n , $\partial_t X(t, n)$ is its speed, and $\partial_n X(t, n)$ is its spacing (headway distance).

⁸If the number of probe vehicles is small, this problem rarely occurs; thus, ad hoc data cleansing can work. Otherwise, it can be troublesome.

models. Meanwhile, instead of analytically deriving stochastic models from their sources, many studies have constructed stochastic models by simply adding random noise into the numerical schemes of the deterministic traffic flow models. In the latter studies, Monte Carlo simulation is often used to compute the model easily (Section 5.1.2), so that analysis on theoretical properties of the models—which is generally challenging—are not required.

3.2.3. Numerical schemes

Numerical schemes such as finite difference methods (FDMs) are common to solve traffic PDEs numerically.⁹ Typically, state variables in a domain within given boundaries can be computed based on given boundary conditions using the proper numerical schemes. For proper approach to this problem, one needs to consider the appropriate discretization of the corresponding boundary value problem (BVP) (Evans, 1998; Garavello et al., 2016)

Standard numerical schemes based on FDMs (c.f., LeVeque, 1992) has been widely used for computing numerical solutions to these problems, such as the Godunov scheme (Lebacque, 1996), an upwind scheme (Leclercq et al., 2007), Lax–Friedrichs scheme (i.e., first order scheme) (Wong and Wong, 2002; Göttlich et al., 2013), and Lax–Wendroff scheme (i.e., second-order scheme) (Michalopoulos et al., 1993). In particular, to compute PW-like models, specific FDMs for the models have been extensively used (Papageorgiou et al., 1989). However, it is known that the first-order schemes are diffusive in general, which can be problematic for accuracy when reproducing heads and ends of traffic jams; and the second-order schemes oscillate. Nevertheless, the Godunov scheme (Godunov, 1959) has been widely applied for traffic flow models, such as the LWR model (Daganzo, 1994; Lebacque, 1996) and ARZ model (Mammar et al., 2009) because of its accuracy and generality. In particular, a simplified case of the scheme for the LWR model, namely one with triangular or trapezoidal FDs and discretized with the Courant–Friedrichs–Lewy (CFL) number equal to 1, is often referred to cell transmission model (CTM) (Daganzo, 1994) in transportation engineering and has been widely used because of its reasonable computational cost, accurate shock wave representation, and its solid theoretical basis. However, it is not differentiable in general and therefore may cause technical problems for some TSE approaches (c.f., Section 5.1.2), while other schemes such as upwind and Lax–Friedrichs are differential (Blandin et al., 2012a). For second-order models, Delis et al. (2014) proposed high-resolution methods, which are more accurate and do not oscillate.

Switching mode models (SMMs) are efficient computation methods for solution of the LWR model (e.g., Muñoz et al., 2006). They are piecewise linearization of the CTM and consist of a discrete set of “modes” that represents the current regime (free-flowing or congested) of traffic on road segments. By using an SMM, traffic dynamics can be efficiently computed once the current mode is identified in some manner. Several extensions have been proposed following this idea, such as considering uncertainty (e.g., Sumalee et al., 2011; Morbidi et al., 2014) and reducing the size of a set of modes to enable large-scale computation (e.g., Canudas de Wit et al., 2012; Thai and Bayen, 2015).

For the LWR model, the exact solution can be efficiently obtained by using techniques in the HJ PDE theory, such as the Hopf–Lax (HL) formula (Evans, 1998). Several methods have been developed in a similar manner, for example, exact methods with triangular FD, known as Newell’s minimization principle and variational theory (VT) within the transportation community (Newell, 1993a,b,c; Daganzo, 2005a,b), a method that can manage internal boundary conditions based on the HL formula (Claudel and Bayen, 2010a,b), and an exact method with arbitrary FD (Mazaré et al., 2011). Solution methods in Lagrangian coordinates have also been developed (Newell, 2002; Leclercq et al., 2007; Han et al., 2012), which are, in fact, equivalent to VT/HL in Eulerian coordinates (Daganzo, 2006; Laval and Leclercq, 2013). For the details on these methodologies, see Daganzo (2006), Aubin et al. (2008), Claudel and Bayen (2010a,b), and Laval and Leclercq (2013).

Regarding boundary conditions, the most common boundary of a domain is a rectangle in the model’s coordinate system, for example, two locations and two time instants in an Eulerian coordinates system, and two vehicles’ trajectories and two locations or two time instants in Lagrangian coordinates systems. More complex boundaries, such as an arbitrarily closed loop (Daganzo, 2005a) and internal boundaries (Claudel and Bayen, 2010a), are sometimes defined if necessarily. If the domain is on a road network, the flow from sink/source nodes can be also be a boundary condition (c.f., Section 3.3).

Application to TSE: The most commonly used schemes in TSE studies are as follows: SMMs for efficient computation (e.g., Muñoz et al., 2003), the Godunov scheme (e.g., Haj-Salem and Lebacque, 2002; Mihaylova and

⁹In the case of the LWR PDE and extensions, FDMs have been than more prevalent than finite volume methods. An example of few exceptions is Tchakian and Zhuk (2015) which applied a finite volume method to LWR-based TSE.

Boel, 2004), the FDM for PW-like models (e.g., Nanthawichit et al., 2003; Wang and Papageorgiou, 2005), and HL/VT for the exact computation of the LWR model (e.g., Claudel and Bayen, 2008; Laval et al., 2012). Choosing a numerical scheme requires considering estimation approaches and input data. For example, some accurate numerical schemes (e.g., the Godunov scheme) cannot be incorporated into certain computationally efficient estimation approaches (Blandin et al., 2012a). Using disaggregated mobile data requires specific schemes (e.g., HL, VT, Lagrangian coordinates) because of their different nature compared with stationary data. For the details, see Sections 4.2 and 5.1.2. Some recent studies have begun to consider new options, such as the Fourier–Galerkin (FG) method and discontinuous Galerkin (DG) method for minimax estimation (Tchraikian and Zhuk, 2015; Tchraikian et al., 2015) and spectral method (Xia et al., 2017).

3.3. Node models

Node models, also referred to as junction and intersection models, are required to model traffic on a network. They connect links and determine merge and diverge flows that depend on the states of the links. In the case of highways, junctions connecting multiple highway routes and on/off-ramps are considered as nodes. Additionally, a multi-lane link is sometimes modeled as a network of single-lane links (e.g., Laval and Daganzo, 2006). Several models that corresponds to different link models have been proposed. Essentially, a node model has to determine and integrate two factors: supply (i.e., receiving flow) of the downstream links and demand (i.e., sending flow) of the upstream links (Lebacque, 1996; Jin et al., 2009). Supply is the maximum flow that is received by the downstream link. It is determined by the geometric structure of the node and links and traffic situation in the downstream link. Demand is the maximum flow that is sent from the upstream link. It is determined by the geometric structure, traffic situation in the upstream link, and driver behavior such as route choice. If a node is at the boundary of the network, boundary demand (e.g., on-ramp flow from arterial street) should be considered; its explicit modeling requires driver behavior models, again. Therefore, this problem is still an open question because the many factors are dominated by human behavior, which is uncertain due to possible irrationality and incomplete information for both of driver and road administrator (Bliemer et al., 2017). For the details on node models and networks, see Garavello et al. (2016) and references therein.

Application to TSE: In the context of TSE, the node model has been paid little attention. Although several studies have investigated TSE in a large-scale network using certain node models (e.g., Wang et al., 2006; Zuurbier et al., 2006), the importance of node models for TSE has not been investigated fully and is still the focus of ongoing work, with the changing landscape of traffic information (Garavello et al., 2016). In particular, node models that describe route choice at nodes that are responsive to the traffic situation and information (e.g., drivers avoiding congestion) have not been incorporated into TSE. This might be because such route choice behavior is uncertain and makes the problem complex (Tampère and Immers, 2007). Regarding boundary demand, some studies have incorporated demand estimation/prediction in their TSE methods, and the importance of demand estimation has been pointed out (e.g., Wang and Papageorgiou, 2005; Wang et al., 2006; Zhang and Mao, 2015).

4. Data

In this section, we introduce available traffic measurement data used for TSE. In general, they can be grouped into two categories based on their nature: stationary and mobile data. In addition, we introduce another independent categorization: disaggregated and aggregated. Fig. 9 illustrates this categorization. These types of data are utilized in either streaming and historical manner in TSE. For practical perspectives on traffic data collection, see Leduc (2008).

4.1. Stationary data

Stationary sensors (e.g., inductive loop detectors, ultrasonic detectors, radar detectors, and closed-circuit television cameras) can collect traffic data that consists of every vehicle at their installed locations. Using typical loop detectors, traffic counts and vehicle occupancy at the location can be measured. The instantaneous vehicle speed at the location is also measured, or inferred from a given vehicle’s body length information. Dual detectors and cameras can measure vehicle trajectories on short road segments directly. These raw data are generally *disaggregated data*, in which an individual vehicle’s information (i.e., trajectory or cumulative flow in the observable area) is contained. Therefore, it can be represented as $N(t, x)$ at a certain x for all t (Fig. 10a). However, because of limitations on data handling (e.g., storage and transmission), the data provided is often converted to *aggregated data*, in which the average traffic state




Figure 9: Categories of traffic data and their examples

at a certain temporal resolution (e.g., 1–5 min) is contained. Such aggregated data can be regarded as “irreversibly compressed” from corresponding disaggregated data. It can be represented as $q(\mathbf{A})$, $k(\mathbf{A})$, and $v(\mathbf{A})$ of Eqs. (1)–(3) where the size of rectangular (on time–space diagram) \mathbf{A} is the aggregation unit Fig. 10b. Stationary data is also known as Eulerian data. These stationary sensors are widely used to collect highway traffic data by road administrators and researchers since the era of [Greenshields \(1935\)](#). However, the amount of data they provide is not always sufficient for traffic control,¹⁰ due to sparse deployment of the sensors (which is due to high installation and maintenance costs of the sensors). For example, usual detector spacing varies from several hundred meters to several kilometers. Moreover, some highways do not have any detectors, especially in rural areas and developing countries. Additionally, their accuracy and precision may be not reliable, for example, because of frequent misses and/or double counting of loop detectors ([Chen et al., 2003](#)).

Application to TSE: Because stationary data are conventional and commonly available on highways in practice, the vast majority of TSE studies use this data. The Eulerian nature of the data is beneficial to be incorporated to the Eulerian traffic flow models which are conventional and common, too. In addition, stationary sensors are often able to measure all traffic state variables; therefore, TSE based only on these data has been well studied (e.g., [Muñoz et al., 2003](#); [Wang and Papageorgiou, 2005](#)). Most of the studies have used aggregated data, whereas few have used disaggregated data (e.g., [Coifman, 2002](#); [Deng et al., 2013](#)). [Coric et al. \(2012\)](#) proposed methods of reconstructing high-resolution data from aggregated detector data, and then investigated effects of reconstruction to TSE accuracy.

4.2. Mobile data

Mobile data is data associated with specific vehicles that usually provides measurements along vehicle trajectory. A typical method to collect mobile data is to use on-vehicle sensors (e.g., GPS, OBD2, and most recently video cameras, radars, etc).¹¹ Such vehicles with sensors are often referred to as *probe vehicles* or *floating cars*. Mobile data collection has been widely enabled by recent advances in ICT (e.g., navigation systems and smartphones). Typical disaggregated mobile data can be represented as $X(t, n)$ for all or specific X , n , and t . Therefore, it is also known as Lagrangian data. Although the use of probe vehicles has received a great deal of attention from the mid-1990s ([Sanwal and Walrand, 1995](#); [Zito et al., 1995](#)), they have been re-recognized as “connected vehicles” in the context of the Internet of Things and vehicle automation at the present time ([Bekiaris-Liberis et al., 2016](#)).

A promising feature of mobile data is that it is possible to collect data from a wider spatiotemporal domain, compared with stationary sensors ([Zito et al., 1995](#); [Herrera et al., 2010](#)), because probe vehicles ultimately have

¹⁰E.g., usual traffic control measures require accurate traffic state information with space resolution of a few hundred meters ([Wang and Papageorgiou, 2005](#)).

¹¹Use of airplanes and satellites (e.g., [Coifman et al., 2006](#)) is notable alternative approach to collect vehicle trajectory in a large area. However, data collected by such approach is not considered as “mobile data” in this article—in fact, such data is similar to “fixed data”, in the sense that it contains trajectories of all vehicles (i.e., it is not sampled data associated with vehicles).




Figure 10: Illustration of traffic data on time-space diagrams.




Figure 11: Disaggregated and aggregated data from GPS probe vehicles (adapted from [Work et al. \(2010\)](#)).

broader coverage of the road network. The data is continuously collected while the probe vehicles are driving. Two important characteristics of probe vehicle data are *penetration rate* and *temporal sampling rate*. The penetration rate is defined as the ratio of probe vehicles to all traffic. The temporal sampling rate is defined as the time interval for the consecutive reporting of data. In general, it is preferable if penetration rate (in proportion) and temporal sampling rate (in frequency) are high.

GPS (i.e., global navigation satellite system) is the most typical on-vehicle sensor ([Herrera et al., 2010](#)). Its raw data is generally disaggregated data, which is an individual probe vehicle's continuous trajectory (Fig. 10c). However, aggregated data, which consists of average speed with a certain spatiotemporal resolution (Fig. 10d), is widely used in practical situations. Fig. 11 illustrates this kind of mobile data. The sampling and aggregation policies are in general driven by privacy consideration ([Krumm, 2009](#); [Hoh et al., 2012](#)).

Other advanced on-vehicle sensors, such as OBD2, can also be used to collect mobile data. An example is a range finder (e.g., radar, lidar, and a stereo camera), which is now being equipped for vehicle automation purposes, known as advanced driver assistance system (ADAS) ([Bengler et al., 2014](#)) and autonomous vehicles. It provides novel information about traffic; for example, it can observe local traffic density, which is approximately the inverse of bumper-to-bumper distance, near a probe vehicle ([Seo et al., 2015a](#)). These new data types, in addition to conventional positioning data, have been named *extended floating car data (xFCD)* ([Huber et al., 1999](#)).

The connection to vehicular ad hoc networks (VANET), by which a probe vehicle can count and report the number of nearby connected vehicles ([Darwish and Abu Bakar, 2015](#)), is utilized to collect and transmit traffic data. If all the vehicles are equipped with VANET and their connectivity is high, the traffic density can be directly determined (e.g., [Panichpapiboon and Pattara-atikom, 2008](#)).¹²

Travel time information (TTI) of a vehicle between distant locations can be considered as disaggregated probe vehicle data with a long temporal sampling interval. It is collected by using either automatic vehicle identification system¹³ or mobile communication instruments.¹⁴ Especially, the CDR and MAC address data has been paid great deal of attention because of wide spread of mobile phones in these days and their less dependency to infrastructure. The travel time is measured between either within-link locations (i.e., multiple dots in a link) or inter-link locations (i.e., one or zero dot in a link). The latter has unique feature compared with other data. That is, travel route is not necessarily identified and therefore required to be inferred ([Wu et al., 2015](#)). Because of the TTI's wide-ranging

¹²In this kind of VANET-based TSE, an essential problem is the connectivity of VANET, rather than traffic flow models or estimation approaches which are the focus of this article. Such connectivity is a highly technical problem; thus, it is out of scope for this article. For the details, see survey articles by [Song and Lee \(2013\)](#); [Darwish and Abu Bakar \(2015\)](#), dedicated to this and other VANET-specific problems.

¹³It matches a vehicle at distant locations based on the vehicle's features, such as license plate number ([Kanayama et al., 1991](#)), electromagnetic features of the vehicle's body ([Coifman, 1998](#)), and visual features ([Sumalee et al., 2012](#))

¹⁴E.g., media access control (MAC) address ([Wasson et al., 2008](#); [Barceló et al., 2010](#)), CDR (call digital records) ([Caceres et al., 2007](#); [Wu et al., 2015](#)) and similar data from mobile phones ([Asakura and Hato, 2004](#))

nature, it has been used for large-scale estimation problems, such as travel time measurement (e.g., [Coifman, 1998](#)), origin-destination matrix estimation (e.g., [Asakura et al., 2000](#); [White and Wells, 2002](#); [Caceres et al., 2007](#); [Barceló et al., 2010](#)), and route choice estimation (e.g., [Wu et al., 2015](#); [Yang and Sun, 2015](#)).

A problem with mobile data is that its sampling and potential biases. For example, if probe vehicles belong to a logistic fleet, they may travel at a slower speed than average. In addition, vehicles with recent advanced driving technologies (e.g., ADAS and connected vehicles), which may tend to act as probe vehicles, may show different driving characteristics compared with fully manual vehicles, and progressively change driving and traffic patterns.

Application to TSE: Mobile data has received a great deal of attention in TSE recently. Some studies have used both mobile and stationary data, others have mainly used mobile data together with limited stationary data, and a few studies have used mobile data only. Because of its nature (i.e., sampled data), mobile data is used in notably different manners compared with conventional TSE methods using stationary data.

For model-driven TSE, incorporating some of the mobile data (i.e., GPS probe vehicle and TTI) requires special techniques. This is because such mobile data only contain average speed or sampled trajectories data. This means that other traffic state variables (i.e., flow and density) cannot be determined from it without additional assumptions. Moreover, in conventional traffic flow models (e.g., the LWR model with an Eulerian coordinate system), the state variable is density; this may be due to that the conventional models have been developed based on empirical observation from the stationary sensors. Unfortunately, it is known that mapping from speed to density via an FD can be erroneous, especially in free-flowing regimes ([Herrera and Bayen, 2010](#)).¹⁵ To account for this problem, several approaches have been proposed. For aggregated GPS probe vehicle data, [Nanthawichit et al. \(2003\)](#) used a second-order traffic flow model to combine probe vehicle data with stationary data. [Work et al. \(2008, 2010\)](#) developed a first-order traffic flow model whose state variable is speed. [Kesting and Treiber \(2009\)](#) introduced a shock wave detection method based on probe vehicle data. [van Lint and Hoogendoorn \(2010\)](#) and [Treiber et al. \(2011\)](#) used an adaptive smoothing filter (ASF) to combine probe vehicle data with stationary data. [Herrera and Bayen \(2010\)](#) implemented the Newtonian relaxation method to use the erroneous FD-based mapping. For disaggregated GPS probe vehicle data, [Claudel and Bayen \(2008, 2011\)](#) developed an HL-based incorporation method, which considered probe vehicle data as internal boundary conditions. [Yuan et al. \(2012\)](#) used the LWR model with the Lagrangian coordinate system. [Deng et al. \(2013\)](#) and [Kuwahara et al. \(2013\)](#) defined cumulative flow as state variables using VT. [Piccoli et al. \(2013, 2015\)](#) developed mapping methods from trajectories to traffic states based on PTMs. [Xia et al. \(2017\)](#) formulated a method that could explicitly consider vehicle trajectories in the Eulerian LWR model. [Bucknell and Herrera \(2014\)](#) investigated effects of penetration rate and temporal sampling rate of GPS probe vehicles to accuracy of a TSE method.

Some data-driven methods have used aggregated GPS probe vehicle data. Essentially, they first extracted an FD or similar relations from historical stationary data, and then estimated traffic states from mobile data and the FD-like relation (e.g., [Blandin et al., 2012b](#); [Neumann et al., 2013](#)). [Wilby et al. \(2014\)](#) proposed a TSE method using xFCD with a similar approach.

All the aforementioned methods require calibrated FDs or similar relations. Therefore, even if they mainly use mobile data, they essentially require stationary data for FD calibration (c.f., Section 3.1). This implies that the application of these studies in wide-ranging areas is still difficult. To account for this problem, FD-free TSE using mobile data has been investigated. Particularly, streaming-data-driven TSE methods using conventional mobile data and limited stationary data (e.g., detectors at boundaries) have been proposed by [Coifman \(2003\)](#); [Astarita et al. \(2006\)](#); [Qiu et al. \(2010\)](#); [Bekiaris-Liberis et al. \(2016\)](#). They rely on the CL of traffic, which is likely to be satisfied under common traffic situations. Other studies have investigated the use of advanced mobile data with no stationary data. [Wardrop and Charlesworth \(1954\)](#) proposed the use of xFCD (manually collected at that age) to estimate the traffic state—in fact, this might be the most ancient TSE study using mobile data. After recent technological advances, some applications of advanced mobile data have been proposed. [Seo et al. \(2015a\)](#) proposed a streaming-data-driven TSE method using xFCD. Then, [Seo and Kusakabe \(2015\)](#) incorporated the method into a CL. To the best of the authors' knowledge, these are the only methods that implement TSE with mobile data only.¹⁶ [Seo et al. \(2015b\)](#) extended the method as a model-driven method, where its FD was endogenously calibrated.

¹⁵In fact, this implies that the equilibrium assumption in the LWR model is not very accurate.

¹⁶Exceptions are VANET-based TSE methods, which assume that all vehicles report their position via VANET (e.g., [Panichpapiboon and Pattara-atikom, 2008](#)).

Subject to TTI, within-link matching information has been used in some studies. [Cheng et al. \(2006\)](#) used CDR to derive traffic speed; however, they reported it caused excessive error. [Gundlegard et al. \(2015\)](#) developed a method of combining mobile datasets with various temporal sampling rate, such as TTI and GPS, for accurate estimation. [Deng et al. \(2013\)](#) combined TTI with other mobile and stationary data, considering the heterogeneity of these different data. [He et al. \(2016\)](#) used CDR to determine the average speed on a long highway route. [Coifman \(2003\)](#) used TTI in his streaming-data-driven TSE method. To the best of the authors’ knowledge, inter-link matching information has not been used in TSE studies.

Regarding the bias in mobile data specific to the TSE problem, to the best of the authors’ knowledge, no studies have investigated this problem.

5. Estimation approaches

TSE approaches, which may be based on the models and data that we discussed in previous sections, are summarized in this section.

5.1. Model-driven approaches

In this article, a model-driven TSE method is defined as a TSE method which is based on physical traffic flow models (c.f., Section 3). It relies on explicit a priori knowledge of traffic dynamics to estimate the traffic state based on partial observation.

The advantages are as follows: first, if the model is representative of the physics of traffic, it should add value to the observation. Therefore, the method may estimate an accurate traffic state with less input data. In addition, it has high explanatory power. This means that even if the estimation is inaccurate, it would be possible to identify the reasons as well as confidence intervals. Moreover, it can be integrated with traffic control operations directly, for example, by using model predictive control. The disadvantage is that, in the case of poor model or poorly calibrated models, such models can lead to poor performance of the TSE. Therefore, model-driven TSE requires careful selection and calibration of models, depending on the application. In some cases, checking the validity of a model or calibrating a model requires a large amount of data.

5.1.1. BVP

As mentioned in Section 3.2.3, numerical schemes have been developed to solve BVPs numerically. In many model-driven TSE studies, the boundary conditions are observed or given. Therefore, solving BVPs can be regarded as TSE where the boundary conditions and model are assumed to be correct (obviously, this is forward simulation rather than estimation; this distinction is not always clear in some of the TSE literatures).

Several studies have proposed TSE simply based on BVPs. [Coifman \(2002\)](#) proposed a calculation method for vehicle trajectories from disaggregated stationary data based on application of the LWR model. [Laval et al. \(2012\)](#) developed a stochastic extension to Newell’s principle to estimate traffic states with their confidence intervals. [Kuwahara et al. \(2013\)](#) used VT to combine stationary and mobile data. [Blandin et al. \(2013\)](#) and [Fan et al. \(2014\)](#) used PTM and ARZ-like models, respectively, to estimate non-stationary traffic.

5.1.2. Data assimilation

Data assimilation (DA) or inverse modeling are two terms sometimes interchangeably used to refer to the problem of estimation (or inference) and model calibration (or system identification) respectively ([Chen, 2003](#); [Evensen, 2009](#)). For DA-based TSE, traffic flow models and data are no longer considered as perfect. Instead, the approach estimates “the most probable state” which may not be identical to both model prediction and observation. In other words, it allows observation to correct the model’s prediction. This approach has the benefit of integrating the modeling and measurement error which we discussed in previous sections. Therefore, the DA approach is widely employed by TSE studies. To the authors’ knowledge, use of DA for TSE is firstly proposed by [Szeto and Gazis \(1972\)](#).

The Kalman filter (KF) and its extensions and variations (KFTs: KF-like techniques) are among the most well-known implementation of DA. In general, the KFTs are based on the state-space model:

$$\mathbf{x}_t = \mathbf{f}_t(\mathbf{x}_{t-1}, \boldsymbol{\nu}_t), \quad (14)$$




Figure 12: DA and TSE.

$$y_t = h_t(x_t, \omega_t), \quad (15)$$

where x_t is a state vector, f_t is a system model, v_t is system noise, y_t is an observation vector, h_t is an observation model, and ω_t is observation noise at time t . Eq. (14) is referred to as a system or process equation and represents the dynamics of the system. Eq. (15) is referred to as an observation or measurement equation and represents the observation of the system. The main objective of the KFTs is to obtain the x_t that maximizes $p(x_t|y_1, y_2, \dots, y_t)$. In other words, the KFTs estimates the most probable state variables with respect to an available observation, assumed system model, and noises. For the details on DA and KFTs, see [Chen \(2003\)](#); [Evensen \(2009\)](#); [Higuchi \(2011\)](#); [Van Leeuwen et al. \(2015\)](#) (description on KFTs in this section is mainly based on [Higuchi \(2011\)](#)). Fig. 12 illustrates a framework of DA in TSE.

In the TSE context, the state vector x_t often corresponds to a discretized traffic state or cumulative flow that is the subject of the TSE. Then, f_t generally represents the numerical scheme used for the continuous PDE traffic flow model (Section 3.2.3), to which model noise is added. The model parameters, such as the FD parameters, are either endogenously estimated together with the traffic state or exogenously assumed, as discussed in Section 3.1 (this problem is often referred to as system identification or model calibration ([Ljung, 1998](#))). The former is performed using various techniques, such as defining a state vector that includes model parameters (e.g., [Wang and Papageorgiou, 2005](#); [Wang et al., 2009](#)) and applying a dual filter (e.g., [van Lint et al., 2008](#)). The latter makes the problem simple; however, it requires an independent (offline) parameter calibration procedure, which may cause the aforementioned problems. The system noise v_t encompasses the modeling error or uncertainty. Some studies have explicitly modeled noise from its source (e.g., [Sumalee et al., 2011](#); [Laval et al., 2012](#); [Kurzhanskiy and Varaiya, 2012](#)), whereas many others have assumed that the noise is simple white noise with a given deviation, which means that it may require another calibration. The observation vector y_t corresponds to traffic data; and the observation model h_t corresponds to a mapping from the traffic state to observed traffic data. A linear observation model, which means that the state variables are directly observed, is often employed. For the case of stationary data, either aggregated or disaggregated, it is easy to construct an observation model for a conventional traffic flow model (i.e., a Eulerian coordinate system-based model with density or cumulative flow as the state variable) in a straightforward manner. For the case of mobile data, some techniques are required, as discussed in Section 4.2, and can pose some problems when penetration rate or temporal sampling rate is low. Observation noise ω_t represents measurement errors, which are usually known from the technical specification of sensors. There are various implementations of the KFTs that assume different conditions to Eqs. (14) and (15). The following explains the most representative implementations together with their applications and features for TSE.

The KF is the most basic KFT as the name suggests. It assumes that both the system and observation models are linear (e.g., $x_t = F_t x_{t-1} + G_t v_t$). The KT is efficient to compute; however, as standard traffic flow models are

clearly nonlinear, KT has not been widely used in TSE. Some studies have used the KF to exploit its advantage; for example, [Sun et al. \(2003\)](#) and [Thai and Bayen \(2015\)](#) developed an SMM in which the system model f_t behaves linearly and applied the KF (or mixture KF).

The extended Kalman filter (EKF) can use a nonlinear system model to some extent. This is made possible by linearizing the model around the current state (i.e., $F_t = \partial_x f_t(x_{t-1}, \nu_t)$). Because of this beneficial feature, it has been widely used in TSE studies (e.g., [Nanthawichit et al., 2003](#); [Wang and Papageorgiou, 2005](#); [Schreiter et al., 2010](#)). Note that a common mistake perpetrated in the literature (knowingly or not, ignored on purpose or not) is to use EKF technique on models that are not differentiable, such as the Godunov discretization of the (Eulerian) LWR model, including CTM ([Blandin et al., 2012a](#)). The linearization can be based on either an analytical or numerical differential. An analytical differential approach is preferable as a numerical differential induces numerical error. However, it is known that some of accurate numerical schemes, such as the Godunov scheme for the Eulerian LWR model again, are not differentiable in general ([Blandin et al., 2012a](#)). [Yuan et al. \(2012\)](#) avoided this shortcoming by using the fact that the Godunov scheme can be differential in Lagrangian coordinates. A notable example of accurate and differential schemes is the Lax–Friedrichs scheme used by, for example, [Wong and Wong \(2002\)](#) and [Göttlich et al. \(2013\)](#).

The unscented Kalman filter (UKF) overcomes the shortcomings of the EKF. It can use a nonlinear system model well and does not require an analytical differential. Therefore, it has been used early on for some TSE studies, such as those using Godunov schemes (e.g., [Mihaylova et al., 2006](#)).

The ensemble Kalman filter (EnKF) overcomes the shortcomings of the EKF by employing Monte Carlo simulation. It can use a nonlinear and/or non-differentiable system models well ([Blandin et al., 2012a](#)). Therefore, it has been used often in recent studies (e.g., [Work et al., 2008](#)). The problem is that it can be computationally costly because of the Monte Carlo simulation. Meanwhile, another costliest operations in the aforementioned filters, namely, KF, EKF, UKF, and EnKF, is matrix inversion. To account for this problem, several studies have investigated localization methods ([van Hinsbergen et al., 2012](#); [Sun and Work, 2014](#); [Yuan et al., 2015](#)), so that the size of the matrix can be reduced.

The particle filter (PF) extensively uses Monte Carlo simulation to represent nonlinear phenomena precisely. It has been used in several studies (e.g., [Mihaylova and Boel, 2004](#)). Naturally, it is very computationally costly. In particular, the curse of dimensionality makes it essentially difficult to apply to large-scale estimation. However, at the same time, the PF has a promising feature in terms of computational cost: unlike other filters, it does not require matrix inversion. It means that the PF can be parallelized easily and is therefore scalable ([Hegyi et al., 2007](#); [Mihaylova et al., 2012](#)). [Wright and Horowitz \(2016\)](#) applied Rao–Blackwellized PF for efficient computation.

Other methods that are not based on the KFTs have been also proposed. The ASF (adaptive smoothing filter) developed by [Treiber and Helbing \(2002\)](#) specifically for TSE has been used to combine multiple sensing data. It relies on the constant wave speed (i.e., information propagation speed) in each of the free-flowing and congested regimes; therefore, it can be considered to be based on the LWR model with triangular FD. [Treiber and Helbing \(2002\)](#) used ASF to estimate the traffic state using stationary data. [van Lint and Hoogendoorn \(2010\)](#) and [Treiber et al. \(2011\)](#) developed extensions of ASF to incorporate mobile data as well.

Some studies have reduced a TSE problem to an optimization problem, leveraging mathematical properties of the problem formulation. Convex optimization problems representing TSE have been formulated using theories in HJ PDEs (e.g., [Claudel and Bayen, 2008, 2011](#); [Han et al., 2012](#)). [Deng et al. \(2013\)](#) and [Lei and Zhou \(2014\)](#) formulated optimization problems representing offline¹⁷ TSE. [Sun et al. \(2015\)](#) formulated a least square method that jointly estimates the traffic state and FD parameters.

There are other methods which might not fall in aforementioned conventional class of estimation. [Abouaissa et al. \(2008\)](#) proposed their original method to estimate model parameters jointly. [Herrera and Bayen \(2010\)](#) used the Newtonian relaxation method, which is a heuristic DA technique, to incorporate erroneous mapping from probe vehicle data by changing the model. [Kurzhanskiy and Varaiya \(2012\)](#) developed a TSE method with detailed consideration of uncertainty in models and observation. [Canaud et al. \(2013\)](#) used probability hypothesis density filtering (PHDF) to capture an uncertainty properly like PF, while maintaining a low computational cost. [Piccoli et al. \(2013, 2015\)](#) have developed mapping methods based on features of PTMs to derive traffic state and other variables

¹⁷Offline means “after the data”, when all data has been collected, as opposed to *online* (i.e., using streaming data). This is sometimes also referred to as smoothing in the machine learning community.

from probe vehicle data. [Vivas et al. \(2015\)](#) proposed a distributed consensus-based method to enable large-scale estimation. By nature of the model equations, spectral methods are less common in the field, but have been used; for example, [Tchraikian and Zhuk \(2015\)](#) and [Tchraikian et al. \(2015\)](#) used minimax estimation to implement Galerkin methods as numerical schemes instead of conventional FDMs in order to define flexible resolution. [Nguyen et al. \(2016\)](#) used the adjoint method to estimate model parameters jointly. [Zheng and Su \(2016\)](#) applied compressed sensing (CS) and Markov random field to represent noises more appropriately.

5.2. Data-driven approaches

In this article, a data-driven TSE method is defined as a TSE method that directly relies on historical-data rather than explicit traffic flow models. It mainly uses statistical and ML approaches, and infers real-time traffic states based on dependence found in historical-data. Compared with the model-driven approach, the data-driven approach does not require explicit theoretical assumptions, such as an underlying PDE with FD and a well posed BVP with proper discretization scheme. Additionally, the data-driven approach often rely on relatively simple models; therefore, their computation cost for estimation can be remarkably low. However, a dependency on historical-data means that the methods can fail if irregular events or a long-term trend occurred. The computation cost for training and learning can be significantly high. Moreover, the method can be considered as a “black box,” which means that it is difficult to obtain deductive insights.

Imputation methods have developed to complement missing data caused by malfunctions of detectors and communication. Statistical approaches were often used in early studies. These approaches relied on data from neighboring detectors and time periods. [Smith et al. \(2003\)](#) compares several heuristic methods based on historical-data with a statistical method using a data augmentation technique. A linear regression model using data from spatial neighbor detectors ([Chen et al., 2003](#)), and autoregressive integrated moving average (ARIMA) using time series dataset ([Zhong et al., 2004](#)) are developed. To consider greater complexity of traffic data, several studies have developed methodologies that depend more substantially on historical-data, such as ML and Bayesian statistics. [Ni and Leonard II \(2005\)](#) proposed time series based model incorporating to Bayesian network (BN) to improve bias and robustness of estimation. Kernel regression (KR) ([Yin et al., 2012](#)), fuzzy c-means (FCM) ([Tang et al., 2015](#)), k -nearest neighbors (kNN) ([Tak et al., 2016](#)), and probabilistic principal component analysis (PPCA) ([Li et al., 2013](#)) have been used to incorporate more spatial-temporal information. [Tan et al. \(2014\)](#) developed a method based on robust principal component analysis (RPCA) to consider capacity of traffic flow as well as the temporal correlation. Tensor-based methods using Tucker decomposition (TD) ([Tan et al., 2013](#)) have also been used to consider spatial-temporal information and other information, such as week, day, and hour. [Xu et al. \(2015\)](#) adopted CS to estimate traffic state in large-scale networks. [Ran et al. \(2016\)](#) proposed tensor completion algorithm (HaLRTC) to improve imputing performance. [Duan et al. \(2016\)](#) applied deep learning (DL) (c.f., [Polson and Sokolov, 2017](#)). Bayesian state-space modeling has also been applied to estimate the hidden parameters of the traffic state. [Polson and Sokolov \(2016\)](#) used the Bayesian particle filter (BPF) to estimate traffic state corresponding to free-flowing, breakdown, and recovery regimes.

Several studies have attempted to estimate flow using probe vehicle data. These studies have explored statistical relations between flow and other variables. Essentially, the parameters of TSE models (i.e., concepts similar to an FD) are estimated from historical stationary data, and then streaming mobile data are used for TSE. For example, speed ([Anuar et al., 2015](#); [Neumann et al., 2013](#)), variance of speed ([Blandin et al., 2012b](#); [Bulteau et al., 2013](#)), and other variables in xFCD ([Wilby et al., 2014](#)) are used for such estimation.

It is known that ML can be good at predicting nonlinear phenomena often found in the transportation field ([Karlaftis and Vlahogianni, 2011](#)). However, as shown above, relatively few studies have used ML for TSE. This might be because the physics of link traffic flow has been well understood in previous studies as shown in Section 3.2, and the available models' performance is relatively high for estimation and subsequent control compared with data-driven methods.

Meanwhile, several ML-based approaches can consider some indirectly observed variables of state, such as demand and route choice, which are difficult to be modeled explicitly as mentioned in Section 3.3. For example, this advantage is exploited by short-term future prediction of traffic state ([van Lint and van Hinsbergen, 2012](#); [Vlahogianni et al., 2014](#); [Ermagun and Levinson, 2016](#)). Moreover, for an arterial road (which is a large-scale network connected with unobserved roads and difficult to be described by a physical model), such a hybrid of a traffic flow model and ML

works well for travel time prediction (Herring et al., 2010; Hoffleitner et al., 2012a,b). Therefore, such use of ML might be beneficial for particular highway TSE.

5.3. Streaming-data-driven approaches

In this article, a streaming-data-driven TSE method is defined as a TSE method that rely on streaming data and “weak” assumptions, such as random sampling condition and CL. It does not rely on “strong” assumptions characterized by empirical relation, such as PDE models and FDs (as in model-driven approaches), nor dependency in historical-data (as in data-driven approaches). This means that the method requires less a priori knowledge and no historical-data; thus, it is robust against uncertain phenomena and unpredictable incidents. At an age of near ubiquitous sensor (e.g., cell phone) penetration, and with the massive emergence of connected vehicles, this approach might become prevalent in the near future. The limitation of streaming-data-driven approach is that they may require massive streaming data in order to perform accurate estimation. In addition, the approach itself does not have any future prediction capability.

Wardrop and Charlesworth (1954) proposed the moving observer method, which is TSE using vehicles that counts nearby vehicles. Florin and Olariu (2017) proposed a modern variant of the moving observer method. By assuming a random sampling condition only, Seo et al. (2015a) proposed TSE methods using vehicles that measure spacing (i.e., xFCD).

The CL is a principle in traffic flow theory and considered as physically reasonable without empirical justification (Papageorgiou, 1998). Vehicle trajectories (i.e., disaggregated probe vehicle data) are useful information to be incorporated with the CL, because the number of vehicles between two vehicles will be conserved because of the CL if there is no lane-changing. Although this is not exactly the case in practice due to lane-changing, it can be a reasonable assumption if a sufficiently wide area is considered where effects of lane-changing can be ignored; in this sense, it can be considered as a “weak” assumption. Several studies have proposed TSE methods based on this idea. Coifman (2003) used disaggregated data from TTI and detectors to estimate density. Its notable feature is that it considers and estimates lane-changing flow as well. Astarita et al. (2006) and Qiu et al. (2010) used aggregated and disaggregated, respectively, probe vehicle data and a limited number of detectors (e.g., at the entrance and exit). Bekiaris-Liberis et al. (2016) combined this approach with the KF, whose system model represents the CL. Seo and Kusakabe (2015) combined disaggregated spacing probe vehicle data with the CL.

6. Summary of the survey

In this article, we have provided a comprehensive survey of existing methods for highway TSE problem. Existing TSE methods were characterized according to three elements which are fundamental to TSE: estimation approach, traffic flow model, and input data. Then their basic features, advantages, and disadvantages were discussed. The results would be useful for assessing the applicability of a TSE method and determining future research directions.

6.1. Current state

Tables 1–4 show comprehensive lists of existing TSE methods with their main characteristics, namely estimation approach, traffic flow model, and input data. For the notation, see Appendix A.

From these tables, progress and the current state of TSE can be surveyed at a glance. In summary:

1. The model-driven approach has been extensively studied. It is predominated both in the traffic engineering and in the control/optimization literature. This might be because of decades of extensive work of modelers.
2. For the model-driven approach, the LWR model is widely used. This might be because of its simplicity and compactness. Use of Godunov scheme for the LWR model is also popular.
3. For the model-driven approach, the KFTs are widely used probably because it leads itself well to discretization of PDE models. Recent studies have begun to incorporate several new frameworks, such as convex optimization.
4. The use of mobile data has received a considerably amount of attention recently, since the era of so-called Internet of Things, the emergence of the mobile internet, and crowd sourcing traffic information data. However, most of the mobile data-based TSE methods today still requires stationary data.

5. The use of disaggregated data has received some attention recently. This might because of theoretical advances in traffic flow models, combined with the aforementioned technology progress.
6. Data-driven and streaming-data-driven approaches appear to have received more attention recently, probably because of high data availability in these days.

6.2. Future research directions

Based on the survey results, considerable future research directions can be suggested.

The use of disaggregated data has begun to receive significant attention. Simultaneously, data availability continues to increase in terms of both quantity (e.g., penetration rate of probe vehicles) and quality (e.g., xFCD and TTI), making TSE a beneficiary of this trend. However, this may result in some theoretical challenges for model-driven TSE because of discrepancies between the single-lane single-class traffic flow models, which have been widely used in current studies, and actual disaggregated data, which is collected from a multi-lane multi-class environment (c.f., Sections 3.2.2 and 4.2). To account for this problem, the development and use of Lagrangian multi-lane multi-class models (e.g., Yuan, 2013; Costeseque and Duret, 2016), which are challenging tasks, for TSE could be considered. The use of data-driven or streaming-data-driven approaches (which recent studies have begun to consider) would be also valuable, as they do not require explicit traffic flow models. Regarding application of TSE, such high-resolution traffic states will be valuable for using automated vehicle technologies, such as lane-changing and merging assistance, which require lane-scale detailed traffic state information (Diakaki et al., 2015).

The bias in mobile data is an important problem (c.f., Sections 3.2.2 and 4.2). To solve this problem, Lagrangian multi-lane multi-class models would be useful because they can track specific vehicles by considering their characteristics.

Traffic demand, both at boundaries and junctions (c.f., Section 3.3), is often neglected by TSE studies (e.g., simply assumed to be observed or inferred from historical-data). This is partially accounted for by existing studies, such as the estimation of boundary flow (e.g., Wang et al., 2006; Zhang and Mao, 2015); however, demand responsive to traffic has not been well investigated in TSE. This problem would be significant for TSE in large-scale networks. One of the reasons for a lack of such studies might be the modeling difficulty caused by the uncertainty of human behavior. To account for this problem, the incorporation of ML could be considered because it works well for the case of arterial roads (Herring et al., 2010; Hofleitner et al., 2012a,b). The use of inter-link TTI data, which has not been used by current TSE (c.f., Section 4.2), would be valuable data for this problem, since the data represent route choice behavior of large number of road users. Additionally, to enable such large-scale estimation, it is necessary to extensively develop and implement computationally efficient techniques, such as numerical schemes (e.g., Muñoz et al., 2006), localization (e.g., van Hinsbergen et al., 2012), and parallelization (e.g., Hegyi et al., 2007).

Acknowledgements

The part of this research is financially supported by the Japan Society for the Promotion of Science (KAKENHI Grant-in-Aid for JSPS Fellows 14J10218, Young Scientists (B) 16K18164, and Scientific Research (S) 26220906). The first author would like to thank Dr. Kentaro Wada (The University of Tokyo), Dr. Wataru Nakanishi (Tokyo Institute of Technology), Dr. Masami Yanagihara (Tokyo Metropolitan University), and Mr. Kouki Satsukawa (The University of Tokyo) for insightful discussion on traffic flow models.

Appendix A. Notation for Tables 1–4

In the “Approach” column, NKF denotes the neural Kalman filter, MKF denotes the mixture Kalman filter, and UPF denotes the unscented particle filter. In the “Model/Name” column, LWR- N indicates that a method uses the LWR model with explicit consideration of vehicle trajectories using, for example, HJ PDE or Lagrangian coordinates. The “Model/external FD?” column indicates whether a method requires external calibration of FD parameters. The “Data/Type” column indicates data used by a method: S denotes stationary data, M denotes mobile data, and (S) indicates that a method requires minimum stationary data (e.g., boundary data) although it mainly uses mobile data. The “Data/Disaggr.?” column indicates whether a method exploits disaggregated data.

Table 1: Summary of model-driven TSE methods.

Study	Approach	Model			Data		Note
		Name	Num. scheme	external FD?	Type	Disaggr.?	
Pourmoallem et al. (1997)	NKF	PW	FDM	yes	S	no	
Coifman (2002)	BVP	LWR- N -like	-	yes	S	yes	
Treiber and Helbing (2002)	ASF	LWR-like	-	yes	S	no	
Muñoz et al. (2003)	SMM	LWR	SMM	yes	S	no	
Nanthawichit et al. (2003)	EKF	PW	FDM	yes	S M	no	
Sun et al. (2003)	MKF	LWR	SMM	yes	S	no	
Mihaylova and Boel (2004)	PF	higher-order	Godunov	yes	S	no	
Wang and Papageorgiou (2005)	EKF	PW-like	FDM	no	S	no	
Cheng et al. (2006)	PF	higher-order	Godunov-like	yes	M (S)	no	cell phone record
Hegyi et al. (2006)	EKF/UKF	PW-like	FDM	no	S	no	comparison among different approaches
Mihaylova et al. (2006)	UKF	higher-order	Godunov	yes	S	no	
Wang et al. (2006)	EKF	PW-like	FDM	no	S	no	network; demand prediction
Zuurbier et al. (2006)	EKF	LWR	Godunov	yes	S	no	network
Hegyi et al. (2007)	PF	PW-like	FDM	yes	S	no	parallel computation
Mihaylova et al. (2007)	PF/UKF	higher-order	Godunov	yes	S	no	comparison among different approaches
Sau et al. (2007)	PF	LWR	Godunov	yes	S	no	
Tampère and Immers (2007)	EKF	LWR	SMM	no	S	no	
Abouaissa et al. (2008)	other	LWR	FDM	no	S	no	parameter estimation-oriented
Claudel and Bayen (2008)	other	LWR- N	HL	yes	S M	yes	
van Lint et al. (2008)	EKF	LWR-like	Godunov	no	S	no	multi-class
Ngoduy (2008)	UKF/UPF	LWR-like	FDM	no	S	no	multi-class
Work et al. (2008)	EnKF	LWR-like	Godunov	yes	M (S)	no	speed-based model
Kesting and Treiber (2009)	other	LWR-like	-	yes	S M	no	shockwave identification using probe vehicles
Wang et al. (2009)	EKF	PW-like	FDM	no	S	no	
Herrera and Bayen (2010)	nudging	LWR	Godunov	yes	M (S)	no	probe data mapping via FD
Schreiter et al. (2010)	EKF	LWR	Godunov	yes	S	no	correction in multiple time steps
van Lint and Hoogendoorn (2010)	ASF	LWR-like	-	yes	S M	no	
Work et al. (2010)	EnKF	LWR-like	Godunov	yes	M (S)	no	speed-based model
Chen et al. (2011)	PF	LWR-like	Godunov	yes	S	no	speed-based model
Claudel and Bayen (2011)	other	LWR- N	HL	yes	S M	yes	LP-based DA; internal boundary condition
Moraescu and Canudas de Wit (2011)	SMM	LWR	SMM	yes	S	no	
Ngoduy (2011)	PF-like	higer-order	FDM	no	S	no	
Sumalee et al. (2011)	SMM	LWR-like	SMM	yes	S	no	stochastic modeling
Treiber et al. (2011)	ASF	LWR-like	-	yes	S M	no	
Canepa and Claudel (2012)	other	LWR- N	HL	yes	S	yes	MLP
Canudas de Wit et al. (2012)	SMM	LWR	SMM	yes	S	no	
Han et al. (2012)	other	LWR- N	HL	yes	S M	yes	
Kurzanskiy and Varaiya (2012)	other	LWR	Godunov	yes	S	no	modeling uncertainty
Laval et al. (2012)	BVP	LWR- N -like	VT	yes	S	no	stochastic modeling
van Hinsbergen et al. (2012)	EKF-like	LWR	Godunov	yes	S	no	localization
Mihaylova et al. (2012)	PF-like	PW-like	FDM	yes	S	no	large scale
Yuan et al. (2012)	EKF	LWR- N	Godunov	yes	M (S)	yes	

Table 2: Summary of model-driven TSE methods (cont.).

Study	Approach	Model			Data		Note
		Name	Num. scheme	external FD?	Type	Disaggr.?	
Blandin et al. (2013)	BVP	PTM	Godunov-like	yes	S	no	modeling uncertainty
Canaud et al. (2013)	PHDF	LWR	Godunov	yes	S	no	
Deng et al. (2013)	other	LWR- N	VT	yes	S M	yes	
Kuwahara et al. (2013)	BVP	LWR- N	VT	yes	M (S)	yes	
Pascale et al. (2013)	PF	LWR-like	Godunov-like	yes	S	no	
Piccoli et al. (2013)	mapping	PTM	-	yes	M	yes	
Wilkie et al. (2013)	EnKF	ARZ	finite volume	yes	S	no	multi-class
Yuan (2013)	EKF	LWR- N	Godunov	yes	M (S)	yes	
Claudel et al. (2014)	other	LWR- N	HL	yes	S M	yes	
Fan et al. (2014)	BVP	ARZ-like	Godunov-like	yes	S	no	LP-based DA; internal boundary condition
Lei and Zhou (2014)	other	LWR- N	VT	yes	S M	yes	LP-based DA
Li et al. (2014)	other	multiple	multiple	yes	S	no	fusing estimation from different traffic flow models
Morbidi et al. (2014)	SMM	LWR	SMM	yes	S	no	distributed local Kalman consensus filter
Polson and Sokolov (2015)	PF	LWR	Godunov	no	S	no	
Sun and Work (2014)	KF-like	LWR	SMM	yes	S	no	
Wang and Work (2014)	EnKF-like	LWR	Godunov	yes	M (S)	no	
Yuan et al. (2014)	EKF	LWR- N	Godunov	yes	S M	yes	
Gundlegard et al. (2015)	EnKF	LWR-like	Godunov	yes	S M	no	
Kuwahara (2015)	BVP	LWR- N	VT	yes	M (S)	yes	network
Lovisari et al. (2015)	other	LWR-like	Godunov	yes	S M	no	
Majid and Abouaïssa (2015)	SMM	LWR	SMM	yes	S	no	
Piccoli et al. (2015)	mapping	PTM	-	yes	M	yes	multi-lane
Seo et al. (2015b)	EnKF	LWR	Godunov	no	M	no	
Sun et al. (2015)	other	LWR- N	VT	no	M S	yes	
Tchrakian and Zhuk (2015)	Minimax	LWR	FG	yes	S	no	least square method
Tchrakian et al. (2015)	Minimax	LWR	DG	yes	S	no	
Thai and Bayen (2015)	KF-like	LWR	SMM	yes	S	no	
Timotheou et al. (2015a)	KF	LWR	SMM	yes	S	no	reduced interactive multiple model KF
Vivas et al. (2015)	other	LWR	SMM	yes	S	no	
Zhang and Mao (2015)	KF-like	LWR	SMM	yes	S	no	
Canepa and Claudel (2016)	other	LWR- N	HL	yes	S M	yes	distributed observer
Duret et al. (2016)	other	LWR- N	VT	yes	S	yes	
He et al. (2016)	EKF	PW-like	FDM	yes	S M	no	
Lovisari et al. (2016)	other	LWR-like	Godunov-like	yes	S M	no	demand uncertainty; interactive multiple model KF
Nguyen et al. (2016)	adjoint	LWR	FDM	no	S	no	
Seo et al. (2016b)	Minimax	LWR	DG	yes	S M	no	
Wang et al. (2016a)	PF-like	LWR	Godunov	yes	M (S)	no	incident detection; efficient multiple model PF
Wang et al. (2016b)	PF-like	LWR	Godunov	yes	M (S)	no	
Wright and Horowitz (2016)	PF-like	higher-order	Godunov-like	yes	S	no	
Zheng and Su (2016)	other	LWR	Godunov	yes	S	no	pseudo-second-order model
Xia et al. (2017)	EnKF/PF	LWR-like	spectral	no	S M	yes	CS and Markov random field
							Eulerian LWR model with explicit vehicle trajectories

Table 3: Summary of data-driven TSE methods.

Study	Approach	Model			Data		Note
		Name	Num. scheme	external FD?	Type	Disaggr.?	
Chen et al. (2003)	regression	-	-	no	S	no	
Smith et al. (2003)	regression	-	-	no	S	no	
Zhong et al. (2004)	ARIMA	-	-	no	S	no	
Ni and Leonard II (2005)	BN and ARIMA	-	-	no	S	no	
Blandin et al. (2012b)	regression	FD-like	-	no	S M	yes	
Yin et al. (2012)	Kernel regression	-	-	no	S	no	
Bulteau et al. (2013)	regression	FD-like	-	no	S M	yes	
Li et al. (2013)	PPCA	-	-	no	S	no	
Neumann et al. (2013)	BN	FD	-	yes	M (S)	no	
Ran et al. (2016)	HaLRTC	-	-	no	S	no	
Tan et al. (2013)	TD	-	-	no	S	no	
Tan et al. (2014)	RPCA	-	-	no	S	no	
Wilby et al. (2014)	regression	-	-	no	S M	yes	xFCD
Tang et al. (2015)	FCM	-	-	no	S	no	
Xu et al. (2015)	CS	-	-	no	S	no	
Anuar et al. (2015)	regression	FD	-	yes	M (S)	no	
Asif et al. (2016)	multiple	-	-	no	S	no	
Duan et al. (2016)	DL	-	-	no	S	no	
Ran et al. (2016)	TD	-	-	no	S	no	
Tak et al. (2016)	kNN	-	-	no	S	no	
Polson and Sokolov (2016)	BPF	-	-	no	S	no	

Table 4: Summary of streaming-data-driven TSE methods.

Study	Approach	Model			Data		Note
		Name	Num. scheme	external FD?	Type	Disaggr.?	
Wardrop and Charlesworth (1954)	-	-	-	no	M	yes	moving observer
Coifman (2003)	-	CL	-	no	S M	yes	
Astarita et al. (2006)	-	CL	-	no	M (S)	no	
Qiu et al. (2010)	-	CL	-	no	M (S)	yes	
Seo et al. (2015a)	-	-	-	no	M	yes	xFCD
Seo and Kusakabe (2015)	-	CL	-	no	M	yes	xFCD
Bekiaris-Liberis et al. (2016)	-	CL	-	no	M (S)	no	
Florin and Olariu (2017)	-	-	-	no	M	yes	moving observer

References

- Abouaissa, H., Fliess, M., Join, C., 2008. Fast parametric estimation for macroscopic traffic flow model, in: Proceedings of the 17th IFAC World Congress.
- Antoniou, C., Balakrishna, R., Koutsopoulos, H.N., 2011. A synthesis of emerging data collection technologies and their impact on traffic management applications. *European Transport Research Review* 3 (3), 139–148.
- Anuar, K., Habtemichael, F., Cetin, M., 2015. Estimating traffic flow rate on freeways from probe vehicle data and fundamental diagram, in: 2015 IEEE 18th International Conference on Intelligent Transportation Systems, pp. 2921–2926. doi:[10.1109/ITSC.2015.468](https://doi.org/10.1109/ITSC.2015.468).
- Asakura, Y., Hato, E., 2004. Tracking survey for individual travel behaviour using mobile communication instruments. *Transportation Research Part C: Emerging Technologies* 12 (3–4), 273–291. doi:[10.1016/j.trc.2004.07.010](https://doi.org/10.1016/j.trc.2004.07.010).
- Asakura, Y., Hato, E., Kashiwadani, M., 2000. Origin-destination matrices estimation model using automatic vehicle identification data and its application to the Han-Shin expressway network. *Transportation* 27 (4), 419–438.
- Asif, M.T., Mitrovic, N., Dauwels, J., Jaillet, P., 2016. Matrix and tensor based methods for missing data estimation in large traffic networks. *IEEE Transactions on Intelligent Transportation Systems* 17 (7), 1816–1825. doi:[10.1109/TITS.2015.2507259](https://doi.org/10.1109/TITS.2015.2507259).
- Astarita, V., Bertini, R.L., d'Elia, S., Guido, G., 2006. Motorway traffic parameter estimation from mobile phone counts. *European Journal of Operational Research* 175 (3), 1435–1446. doi:[10.1016/j.ejor.2005.02.020](https://doi.org/10.1016/j.ejor.2005.02.020).
- Aubin, J.P., Bayen, A.M., Saint-Pierre, P., 2008. Dirichlet problems for some Hamilton–Jacobi equations with inequality constraints. *SIAM Journal on Control and Optimization* 47 (5), 2348–2380.
- Aw, A., Klar, A., Rascle, M., Materne, T., 2002. Derivation of continuum traffic flow models from microscopic follow-the-leader models. *SIAM Journal on Applied Mathematics* 63 (1), 259–278.
- Aw, A., Rascle, M., 2000. Resurrection of “second order” models of traffic flow. *SIAM Journal on Applied Mathematics* 60 (3), 916–938. doi:[10.1137/S0036139997332099](https://doi.org/10.1137/S0036139997332099).
- Barceló, J., Montero, L., Marqués, L., Carmona, C., 2010. Travel time forecasting and dynamic origin-destination estimation for freeways based on Bluetooth traffic monitoring. *Transportation Research Record: Journal of the Transportation Research Board* (1), 19–27.
- Bekiaris-Liberis, N., Roncoli, C., Papageorgiou, M., 2016. Highway traffic state estimation with mixed connected and conventional vehicles. *IEEE Transactions on Intelligent Transportation Systems* 17 (12), 3484–3497.
- Bengler, K., Dietmayer, K., Farber, B., Maurer, M., Stiller, C., Winner, H., 2014. Three decades of driver assistance systems: Review and future perspectives. *Intelligent Transportation Systems Magazine, IEEE* 6 (4), 6–22. doi:[10.1109/ITS.2014.2336271](https://doi.org/10.1109/ITS.2014.2336271).
- Blandin, S., Argote, J., Bayen, A.M., Work, D.B., 2013. Phase transition model of non-stationary traffic flow: Definition, properties and solution method. *Transportation Research Part B: Methodological* 52, 31–55. doi:[10.1016/j.trb.2013.02.005](https://doi.org/10.1016/j.trb.2013.02.005).
- Blandin, S., Couque, A., Bayen, A.M., Work, D.B., 2012a. On sequential data assimilation for scalar macroscopic traffic flow models. *Physica D: Nonlinear Phenomena* 241 (17), 1421–1440. doi:[10.1016/j.physd.2012.05.005](https://doi.org/10.1016/j.physd.2012.05.005).
- Blandin, S., Salam, A., Bayen, A.M., 2012b. Individual speed variance in traffic flow: analysis of Bay Area radar measurements, in: Transportation Research Board 91st Annual Meeting.
- Blandin, S., Work, D.B., Goatin, P., Piccoli, B., Bayen, A.M., 2011. A general phase transition model for vehicular traffic. *SIAM Journal on Applied Mathematics* 71 (1), 107–127.
- Bliemer, M.C.J., Raadsen, M.P.H., Brederode, L.J.N., Bell, M.G.H., Wismans, L.J.J., Smith, M.J., 2017. Genetics of traffic assignment models for strategic transport planning. *Transport Reviews* 37 (1), 56–78. doi:[10.1080/01441647.2016.1207211](https://doi.org/10.1080/01441647.2016.1207211).
- Bucknell, C., Herrera, J.C., 2014. A trade-off analysis between penetration rate and sampling frequency of mobile sensors in traffic state estimation. *Transportation Research Part C: Emerging Technologies* 46, 132–150. doi:[10.1016/j.trc.2014.05.007](https://doi.org/10.1016/j.trc.2014.05.007).
- Bulteau, E., Leblanc, R., Blandin, S., Bayen, A.M., 2013. Traffic flow estimation using higher-order speed statistics, in: Transportation Research Board 92nd Annual Meeting.
- Caceres, N., Wideberg, J., Benitez, F., 2007. Deriving origin destination data from a mobile phone network. *IET Intelligent Transport Systems* 1 (1), 15–26.
- Canaud, M., Mihaylova, L., Sau, J., El Faouzi, N.E., 2013. Probability hypothesis density filtering for real-time traffic state estimation and prediction. *Networks and Heterogeneous Media* 8 (3), 825–842. doi:[10.3934/nhm.2013.8.825](https://doi.org/10.3934/nhm.2013.8.825).
- Canepa, E.S., Claudel, C.G., 2012. Exact solutions to traffic density estimation problems involving the Lighthill–Whitham–Richards traffic flow model using Mixed Integer Programming, in: 2012 15th International IEEE Conference on Intelligent Transportation Systems, IEEE. pp. 832–839.
- Canepa, E.S., Claudel, C.G., 2016. Networked traffic state estimation involving mixed fixed-mobile sensor data using Hamilton–Jacobi equations. *arXiv preprint arXiv:1606.03332*.
- Canudas de Wit, C., Ojeda, L.R.L., Kibangou, A.Y., 2012. Graph constrained-CTM observer design for the Grenoble south ring, in: The 13th IFAC Symposium on Control in Transportation Systems.
- Carey, M., Bowers, M., 2012. A review of properties of flow–density functions. *Transport Reviews* 32 (1), 49–73.
- Cassidy, M.J., 1998. Bivariate relations in nearly stationary highway traffic. *Transportation Research Part B: Methodological* 32 (1), 49–59. doi:[10.1016/S0191-2615\(97\)00012-X](https://doi.org/10.1016/S0191-2615(97)00012-X).
- Chen, C., Kwon, J., Rice, J., Skabardonis, A., Varaiya, P., 2003. Detecting errors and imputing missing data for single-loop surveillance systems. *Transportation Research Record: Journal of the Transportation Research Board* (1855), 160–167.
- Chen, H., Rakha, H.A., Sadek, S., 2011. Real-time freeway traffic state prediction: A particle filter approach, in: 2011 IEEE 14th International Conference on Intelligent Transportation Systems, pp. 626–631.
- Chen, Z., 2003. Bayesian filtering: From Kalman filters to particle filters, and beyond.
- Cheng, P., Qiu, Z., Ran, B., 2006. Particle filter based traffic state estimation using cell phone network data, in: 2006 IEEE 9th International Conference on Intelligent Transportation Systems, pp. 1047–1052.
- Chiabaut, N., Buisson, C., Leclercq, L., 2009. Fundamental diagram estimation through passing rate measurements in congestion. *IEEE Transactions on Intelligent Transportation Systems* 10 (2), 355–359. doi:[10.1109/TITS.2009.2018963](https://doi.org/10.1109/TITS.2009.2018963).

- Claudel, C.G., Bayen, A.M., 2008. Guaranteed bounds for traffic flow parameters estimation using mixed Lagrangian-Eulerian sensing, in: 2008 46th Annual Allerton Conference on Communication, Control, and Computing, pp. 636–645.
- Claudel, C.G., Bayen, A.M., 2010a. Lax–Hopf based incorporation of internal boundary conditions into Hamilton–Jacobi equation. part I: Theory. *IEEE Transactions on Automatic Control* 55 (5), 1142–1157.
- Claudel, C.G., Bayen, A.M., 2010b. Lax–Hopf based incorporation of internal boundary conditions into Hamilton–Jacobi equation. part II: Computational methods. *IEEE Transactions on Automatic Control* 55 (5), 1158–1174.
- Claudel, C.G., Bayen, A.M., 2011. Convex formulations of data assimilation problems for a class of Hamilton–Jacobi equations. *SIAM Journal on Control and Optimization* 49 (2), 383–402.
- Claudel, C.G., Chamoin, T., Bayen, A.M., 2014. Solutions to estimation problems for scalar Hamilton–Jacobi equations using linear programming. *IEEE Transactions on Control Systems Technology* 22 (1), 273–280.
- Coifman, B., 1998. Vehicle re-identification and travel time measurement in real-time on freeways using existing loop detector infrastructure. *Transportation Research Record: Journal of the Transportation Research Board* (1643), 181–191.
- Coifman, B., 2002. Estimating travel times and vehicle trajectories on freeways using dual loop detectors. *Transportation Research Part A: Policy and Practice* 36 (4), 351–364. doi:[10.1016/S0965-8564\(01\)00007-6](https://doi.org/10.1016/S0965-8564(01)00007-6).
- Coifman, B., 2003. Estimating density and lane inflow on a freeway segment. *Transportation Research Part A: Policy and Practice* 37 (8), 689–701. doi:[10.1016/S0965-8564\(03\)00025-9](https://doi.org/10.1016/S0965-8564(03)00025-9).
- Coifman, B., 2014. Revisiting the empirical fundamental relationship. *Transportation Research Part B: Methodological* 68, 173–184. doi:[10.1016/j.trb.2014.06.005](https://doi.org/10.1016/j.trb.2014.06.005).
- Coifman, B., McCord, M., Mishalani, R.G., Iswalt, M., Ji, Y., 2006. Roadway traffic monitoring from an unmanned aerial vehicle. *Intelligent Transport Systems, IEE Proceedings* 153 (1), 11–20.
- Colombo, R.M., 2003. Hyperbolic phase transitions in traffic flow. *SIAM Journal on Applied Mathematics* 63 (2), 708–721. doi:[10.1137/S0036139901393184](https://doi.org/10.1137/S0036139901393184).
- Coric, V., Djuric, N., Vucetic, S., 2012. Traffic state estimation from aggregated measurements with signal reconstruction techniques. *Transportation Research Record: Journal of the Transportation Research Board* (2315), 121–130.
- Costeseque, G., Duret, A., 2016. Mesoscopic multiclass traffic flow modeling on multi-lane sections, in: *Transportation Research Board 95th Annual Meeting*. (hal-01250438v2).
- Daganzo, C.F., 1994. The cell transmission model: A dynamic representation of highway traffic consistent with the hydrodynamic theory. *Transportation Research Part B: Methodological* 28 (4), 269–287. doi:[10.1016/0191-2615\(94\)90002-7](https://doi.org/10.1016/0191-2615(94)90002-7).
- Daganzo, C.F., 1995. Requiem for second-order fluid approximations of traffic flow. *Transportation Research Part B: Methodological* 29 (4), 277–286.
- Daganzo, C.F., 2002. A behavioral theory of multi-lane traffic flow. Part I: Long homogeneous freeway sections. *Transportation Research Part B: Methodological* 36 (2), 131–158. doi:[10.1016/S0191-2615\(00\)00042-4](https://doi.org/10.1016/S0191-2615(00)00042-4).
- Daganzo, C.F., 2005a. A variational formulation of kinematic waves: basic theory and complex boundary conditions. *Transportation Research Part B: Methodological* 39 (2), 187–196. doi:[10.1016/j.trb.2004.04.003](https://doi.org/10.1016/j.trb.2004.04.003).
- Daganzo, C.F., 2005b. A variational formulation of kinematic waves: Solution methods. *Transportation Research Part B: Methodological* 39 (10), 934–950. doi:[10.1016/j.trb.2004.05.003](https://doi.org/10.1016/j.trb.2004.05.003).
- Daganzo, C.F., 2006. On the variational theory of traffic flow: well-posedness, duality and applications. *Networks and Heterogeneous Media* 1 (4), 601–619.
- Darwish, T., Abu Bakar, K., 2015. Traffic density estimation in vehicular ad hoc networks: A review. *Ad Hoc Networks* 24, Part A, 337–351. doi:[10.1016/j.adhoc.2014.09.007](https://doi.org/10.1016/j.adhoc.2014.09.007).
- Del Castillo, J.M., Pintado, P., Benitez, F.G., 1994. The reaction time of drivers and the stability of traffic flow. *Transportation Research Part B: Methodological* 28 (1), 35–60. doi:[10.1016/0191-2615\(94\)90030-2](https://doi.org/10.1016/0191-2615(94)90030-2).
- Delis, A.I., Nikolos, I.K., Papageorgiou, M., 2014. High-resolution numerical relaxation approximations to second-order macroscopic traffic flow models. *Transportation Research Part C: Emerging Technologies* 44, 318–349. doi:[10.1016/j.trc.2014.04.004](https://doi.org/10.1016/j.trc.2014.04.004).
- Deng, W., Lei, H., Zhou, X., 2013. Traffic state estimation and uncertainty quantification based on heterogeneous data sources: A three detector approach. *Transportation Research Part B: Methodological* 57, 132–157. doi:[10.1016/j.trb.2013.08.015](https://doi.org/10.1016/j.trb.2013.08.015).
- Dervisoglu, G., Gomes, G., Kwon, J., Horowitz, R., Varaiya, P., 2009. Automatic calibration of the fundamental diagram and empirical observations on capacity, in: *Transportation Research Board 88th Annual Meeting*.
- Diakaki, C., Papageorgiou, M., Papamichail, I., Nikolos, I., 2015. Overview and analysis of vehicle automation and communication systems from a motorway traffic management perspective. *Transportation Research Part A: Policy and Practice* 75, 147–165. doi:[10.1016/j.tra.2015.03.015](https://doi.org/10.1016/j.tra.2015.03.015).
- Duan, Y., Lv, Y., Liu, Y.L., Wang, F.Y., 2016. An efficient realization of deep learning for traffic data imputation. *Transportation Research Part C: Emerging Technologies* 72, 168–181. doi:[10.1016/j.trc.2016.09.015](https://doi.org/10.1016/j.trc.2016.09.015).
- Duret, A., Leclercq, L., El Faouzi, N.E., 2016. Data assimilation based on a mesoscopic-LWR modeling framework and loop detector data: methodology and application on a large-scale network, in: *Transportation Research Board 95th Annual Meeting*.
- Edie, L.C., 1963. Discussion of traffic stream measurements and definitions, in: Almond, J. (Ed.), *Proceedings of the 2nd International Symposium on the Theory of Traffic Flow*, pp. 139–154.
- El Faouzi, N.E., Leung, H., Kurian, A., 2011. Data fusion in intelligent transportation systems: Progress and challenges—a survey. *Information Fusion* 12 (1), 4–10.
- Ermagun, A., Levinson, D.M., 2016. Spatiotemporal traffic forecasting: Review and proposed directions. Working Paper.
- Evans, L.C., 1998. *Partial Differential Equations*. American Mathematical Society.
- Evensen, G., 2009. *Data assimilation: the ensemble Kalman filter*. Springer Science & Business Media.
- Fan, S., Herty, M., Seibold, B., 2014. Comparative model accuracy of a data-fitted generalized Aw–Rascle–Zhang model. *Networks and Heterogeneous Media* 9, 239–268.
- Florin, R., Olariu, S., 2017. On a variant of the mobile observer method. *IEEE Transactions on Intelligent Transportation Systems* 18 (2), 441–449.

- doi:[10.1109/TITS.2016.2582511](https://doi.org/10.1109/TITS.2016.2582511).
- Garavello, M., Han, K., Piccoli, B., 2016. Models for Vehicular Traffic on Networks. American Institute of Mathematical Sciences.
- Godunov, S.K., 1959. A difference method for numerical calculation of discontinuous solutions of the equations of hydrodynamics. *Matematicheskii Sbornik* 89 (3), 271–306. (in Russian).
- Göttlich, S., Ziegler, U., Herty, M., 2013. Numerical discretization of Hamilton–Jacobi equations on networks. *Networks and Heterogeneous Media* 8 (3).
- Greenshields, B.D., 1935. A study of traffic capacity, in: Highway Research Board Proceedings, pp. 448–477.
- Gundlegard, D., Allstrom, A., Bergfeldt, E., Ringdahl, R., Bayen, A.M., 2015. Travel time and point speed fusion based on a macroscopic traffic model and non-linear filtering, in: 2015 IEEE 18th International Conference on Intelligent Transportation Systems, pp. 2121–2128.
- Haj-Salem, H., Lebacque, J., 2002. Reconstruction of false and missing data with first-order traffic flow model. *Transportation Research Record: Journal of the Transportation Research Board* 1802, 155–165.
- Han, K., Yao, T., Friesz, T.L., 2012. Lagrangian-based hydrodynamic model: Freeway traffic estimation, in: 4th International Symposium on Dynamic Traffic Assignment.
- He, S., Cheng, Y., Ding, F., Zhang, J., Ran, B., 2016. Extended Kalman filter-based freeway traffic state estimation using cellphone activity data, in: Transportation Research Board 95th Annual Meeting.
- Hegyi, A., Girimonte, D., Babuska, R., De Schutter, B., 2006. A comparison of filter configurations for freeway traffic state estimation, in: 2006 IEEE 9th International Conference on Intelligent Transportation Systems, pp. 1029–1034. doi:[10.1109/ITSC.2006.1707357](https://doi.org/10.1109/ITSC.2006.1707357).
- Hegyi, A., Mihaylova, L., Boel, R., Lendek, Z., 2007. Parallelized particle filtering for freeway traffic state tracking, in: Proceedings of the European Control Conference 2007, pp. 2442–2449.
- Helbing, D., 2001. Traffic and related self-driven many-particle systems. *Reviews of Modern Physics* 73, 1067–1141. doi:[10.1103/RevModPhys.73.1067](https://doi.org/10.1103/RevModPhys.73.1067).
- Herrera, J.C., Bayen, A.M., 2010. Incorporation of Lagrangian measurements in freeway traffic state estimation. *Transportation Research Part B: Methodological* 44 (4), 460–481. doi:[10.1016/j.trb.2009.10.005](https://doi.org/10.1016/j.trb.2009.10.005).
- Herrera, J.C., Work, D.B., Herring, R., Ban, X.J., Jacobson, Q., Bayen, A.M., 2010. Evaluation of traffic data obtained via GPS-enabled mobile phones: The Mobile Century field experiment. *Transportation Research Part C: Emerging Technologies* 18 (4), 568–583. doi:[10.1016/j.trc.2009.10.006](https://doi.org/10.1016/j.trc.2009.10.006).
- Herring, R., Hoffleitner, A., Abbeel, P., Bayen, A.M., 2010. Estimating arterial traffic conditions using sparse probe data, in: 2010 IEEE 13th International Conference on Intelligent Transportation Systems, pp. 929–936.
- Higuchi, T. (Ed.), 2011. Introduction to Data Assimilation. Asakura Publishing. (in Japanese).
- van Hinsbergen, C.P.I.J., Schreiter, T., Zuurbier, F.S., van Lint, J.W.C., van Zuylen, H.J., 2012. Localized extended Kalman filter for scalable real-time traffic state estimation. *IEEE Transactions on Intelligent Transportation Systems* 13 (1), 385–394.
- Hoffleitner, A., Herring, R., Abbeel, P., Bayen, A.M., 2012a. Learning the dynamics of arterial traffic from probe data using a dynamic Bayesian network. *IEEE Transactions on Intelligent Transportation Systems* 13 (4), 1679–1693. doi:[10.1109/TITS.2012.2200474](https://doi.org/10.1109/TITS.2012.2200474).
- Hoffleitner, A., Herring, R., Bayen, A.M., 2012b. Arterial travel time forecast with streaming data: A hybrid approach of flow modeling and machine learning. *Transportation Research Part B: Methodological* 46 (9), 1097–1122. doi:[10.1016/j.trb.2012.03.006](https://doi.org/10.1016/j.trb.2012.03.006).
- Hoh, B., Iwuchukwu, T., Jacobson, Q., Work, D., Bayen, A.M., Herring, R., Herrera, J.C., Gruteser, M., Annavaram, M., Ban, J., 2012. Enhancing privacy and accuracy in probe vehicle-based traffic monitoring via virtual trip lines. *IEEE Transactions on Mobile Computing* 11 (5), 849–864.
- Hoogendoorn, S.P., Bovy, P.H.L., 2001. State-of-the-art of vehicular traffic flow modelling. *Proceedings of the Institution of Mechanical Engineers, Part I: Journal of Systems and Control Engineering* 215 (4), 283–303. doi:[10.1177/095965180121500402](https://doi.org/10.1177/095965180121500402).
- Huber, W., Lädke, M., Ogger, R., 1999. Extended floating-car data for the acquisition of traffic information, in: Proceedings of the 6th World Congress on Intelligent Transport Systems, pp. 1–9.
- Jabari, S.E., Liu, H.X., 2012. A stochastic model of traffic flow: Theoretical foundations. *Transportation Research Part B: Methodological* 46 (1), 156–174. doi:[10.1016/j.trb.2011.09.006](https://doi.org/10.1016/j.trb.2011.09.006).
- Jabari, S.E., Liu, H.X., 2013. A stochastic model of traffic flow: Gaussian approximation and estimation. *Transportation Research Part B: Methodological* 47, 15–41. doi:[10.1016/j.trb.2012.09.004](https://doi.org/10.1016/j.trb.2012.09.004).
- Jabari, S.E., Zheng, J., Liu, H.X., 2014. A probabilistic stationary speed–density relation based on Newell’s simplified car-following model. *Transportation Research Part B: Methodological* 68, 205–223. doi:[10.1016/j.trb.2014.06.006](https://doi.org/10.1016/j.trb.2014.06.006).
- Jin, W.L., 2016. On the equivalence between continuum and car-following models of traffic flow. *Transportation Research Part B: Methodological* 93, Part A, 543–559. doi:[10.1016/j.trb.2016.08.007](https://doi.org/10.1016/j.trb.2016.08.007).
- Jin, W.L., Chen, L., Puckett, E.G., 2009. Supply-demand diagrams and a new framework for analyzing the inhomogeneous Lighthill–Whitham–Richards model, in: *Transportation and Traffic Theory 2009: Golden Jubilee*. Springer, pp. 603–635.
- Kanayama, K., Fujikawa, Y., Fujimoto, K., Horino, M., 1991. Development of vehicle-license number recognition system using real-time image processing and its application to travel-time measurement, in: 1991 41st IEEE Vehicular Technology Conference, pp. 798–804.
- Karlaftis, M.G., Vlahogianni, E.I., 2011. Statistical methods versus neural networks in transportation research: Differences, similarities and some insights. *Transportation Research Part C: Emerging Technologies* 19 (3), 387–399. doi:[10.1016/j.trc.2010.10.004](https://doi.org/10.1016/j.trc.2010.10.004).
- Kesting, A., Treiber, M., 2009. Online traffic state estimation based on floating car data, in: *Traffic and Granular Flow '09*.
- Krumm, J., 2009. A survey of computational location privacy. *Personal and Ubiquitous Computing* 13 (6), 391–399.
- Kurzhanskiy, A.A., Varaiya, P., 2012. Guaranteed prediction and estimation of the state of a road network. *Transportation Research Part C: Emerging Technologies* 21 (1), 163–180. doi:[10.1016/j.trc.2011.08.007](https://doi.org/10.1016/j.trc.2011.08.007).
- Kuwahara, M., 2015. Theory, solution method and applications of Kinematic Wave. *Interdisciplinary Information Sciences* 21 (1), 63–75. doi:[10.4036/iis.2015.63](https://doi.org/10.4036/iis.2015.63).
- Kuwahara, M., Ohata, T., Takigawa, T., Abe, K., Watanabe, S., Warita, H., Nakamura, K., Imai, T., Tsuda, H., 2013. Estimating vehicle trajectories on a motorway by data fusion of probe and detector data, in: The 20th ITS World Congress.
- Lamb, H., 1932. *Hydrodynamics*. Cambridge University Press.
- Laval, J.A., Daganzo, C.F., 2006. Lane-changing in traffic streams. *Transportation Research Part B: Methodological* 40 (3), 251–264.

- Laval, J.A., He, Z., Castrillon, F., 2012. Stochastic extension of Newell's three-detector method. *Transportation Research Record: Journal of the Transportation Research Board* 2315 (1), 73–80.
- Laval, J.A., Leclercq, L., 2013. The Hamilton–Jacobi partial differential equation and the three representations of traffic flow. *Transportation Research Part B: Methodological* 52, 17–30. doi:[10.1016/j.trb.2013.02.008](https://doi.org/10.1016/j.trb.2013.02.008).
- Lebacque, J.P., 1996. The Godunov scheme and what it means for first order traffic flow models, in: Lesort, J.B. (Ed.), *Proceedings of the 13th International Symposium on Transportation and Traffic Theory*, Elsevier. pp. 647–677.
- Lebacque, J.P., Mammar, S., Haj-Salem, H., 2007. Generic second order traffic flow modelling, in: Allsop, R.E., Bell, M.G.H., Heydecker, B.G. (Eds.), *Transportation and Traffic Theory 2007*, Emerald. pp. 317–345.
- Leclercq, L., Laval, J.A., Chevallier, E., 2007. The Lagrangian coordinates and what it means for first order traffic flow models, in: Allsop, R., Bell, M., Heydecker, B. (Eds.), *Transportation and Traffic Theory 2007*, Elsevier. pp. 735–753.
- Leduc, G., 2008. Road traffic data: Collection methods and applications. *Working Papers on Energy, Transport and Climate Change*.
- Lei, H., Zhou, X., 2014. Linear programming model for estimating high-resolution freeway traffic states from vehicle identification and location data. *Transportation Research Record: Journal of the Transportation Research Board* 2421 (2421), 151–160.
- LeVeque, R.J., 1992. Numerical methods for conservation laws. Springer Basel AG.
- Li, L., Chen, X., Zhang, L., 2014. Multimodel ensemble for freeway traffic state estimations. *IEEE Transactions on Intelligent Transportation Systems* 15 (3), 1323–1336. doi:[10.1109/TITS.2014.2299542](https://doi.org/10.1109/TITS.2014.2299542).
- Li, L., Li, Y., Li, Z., 2013. Efficient missing data imputing for traffic flow by considering temporal and spatial dependence. *Transportation Research Part C: Emerging Technologies* 34, 108–120. doi:[10.1016/j.trc.2013.05.008](https://doi.org/10.1016/j.trc.2013.05.008).
- Lighthill, M.J., Whitham, G.B., 1955. On kinematic waves. II. a theory of traffic flow on long crowded roads. *Proceedings of the Royal Society of London. Series A, Mathematical and Physical Sciences* 229 (1178), 317–345.
- van Lint, J.W.C., van Hinsbergen, C.P.I.J., 2012. Short term traffic and travel time prediction models, in: *Artificial Intelligence and Advanced Computing Committee, Transportation Research Board (Ed.), Transportation Research Circular*. National Academies Press. E-C168, pp. 22–41.
- van Lint, J.W.C., Hoogendoorn, S.P., 2010. A robust and efficient method for fusing heterogeneous data from traffic sensors on freeways. *Computer-Aided Civil and Infrastructure Engineering* 25 (8), 596–612. doi:[10.1111/j.1467-8667.2009.00617.x](https://doi.org/10.1111/j.1467-8667.2009.00617.x).
- van Lint, J.W.C., Hoogendoorn, S.P., Hegyi, A., 2008. Dual EKF state and parameter estimation in multi-class first-order traffic flow models, in: *Proceedings of the 17th IFAC World Congress*, pp. 14078–14083.
- Ljung, L., 1998. System identification, in: *Signal Analysis and Prediction*. Springer, pp. 163–173.
- Lovisari, E., Canudas de Wit, C., Kibangou, A.Y., 2015. Data fusion algorithms for density reconstruction in road transportation networks, in: *2015 IEEE 54th Conference on Decision and Control*.
- Lovisari, E., Canudas de Wit, C., Kibangou, A.Y., 2016. Density/flow reconstruction via heterogeneous sources and optimal sensor placement in road networks. *Transportation Research Part C: Emerging Technologies* 69, 451–476. doi:[10.1016/j.trc.2016.06.019](https://doi.org/10.1016/j.trc.2016.06.019).
- Majid, H., Abouaïssa, H., 2015. Comparative study of a super-twisting sliding mode observer and an extended Kalman filter for a freeway traffic system. *Cybernetics and Information Technologies* 15 (2), 141–158.
- Makigami, Y., Newell, G.F., Rothery, R., 1971. Three-dimensional representation of traffic flow. *Transportation Science* 5 (3), 302–313.
- Mammar, S., Lebacque, J.P., Haj-Salem, H., 2009. Riemann problem resolution and Godunov scheme for the Aw–Rascle–Zhang model. *Transportation Science* 43 (4), 531–545.
- Mazaré, P.E., Dehwh, A.H., Claudel, C.G., Bayen, A.M., 2011. Analytical and grid-free solutions to the Lighthill–Whitham–Richards traffic flow model. *Transportation Research Part B: Methodological* 45 (10), 1727–1748. doi:[10.1016/j.trb.2011.07.004](https://doi.org/10.1016/j.trb.2011.07.004).
- Michalopoulos, P.G., Yi, P., Lyrintzis, A.S., 1993. Continuum modelling of traffic dynamics for congested freeways. *Transportation Research Part B: Methodological* 27 (4), 315–332.
- Mihaylova, L., Boel, R., 2004. A particle filter for freeway traffic estimation, in: *2004 IEEE 43rd Conference on Decision and Control*, pp. 2106–2111. doi:[10.1109/CDC.2004.1430359](https://doi.org/10.1109/CDC.2004.1430359).
- Mihaylova, L., Boel, R., Hegyi, A., 2006. An unscented Kalman filter for freeway traffic estimation, in: *The 11th IFAC Symposium on Control in Transportation Systems*.
- Mihaylova, L., Boel, R., Hegyi, A., 2007. Freeway traffic estimation within particle filtering framework. *Automatica* 43 (2), 290–300. doi:[10.1016/j.automatica.2006.08.023](https://doi.org/10.1016/j.automatica.2006.08.023).
- Mihaylova, L., Hegyi, A., Gning, A., Boel, R.K., 2012. Parallelized particle and gaussian sum particle filters for large-scale freeway traffic systems. *IEEE Transactions on Intelligent Transportation Systems* 13 (1), 36–48. doi:[10.1109/TITS.2011.2178833](https://doi.org/10.1109/TITS.2011.2178833).
- Morarescu, I.C., Canudas de Wit, C., 2011. Highway traffic model-based density estimation, in: *American Control Conference*, pp. 2012–2017. doi:[10.1109/ACC.2011.5991298](https://doi.org/10.1109/ACC.2011.5991298).
- Morbidi, F., Ojeda, L.L., Canudas de Wit, C., Bellicot, I., 2014. A new robust approach for highway traffic density estimation, in: *European Control Conference*, pp. 2575–2580.
- Moskowitz, K., 1965. Discussion of 'freeway level of service as influenced by volume and capacity characteristics' by D. R. Drew and C. J. Keese. *Highway Research Record* (99), 43–44.
- Muñoz, L., Sun, X., Horowitz, R., Alvarez, L., 2003. Traffic density estimation with the cell transmission model, in: *American Control Conference*, pp. 3750–3755.
- Muñoz, L., Sun, X., Horowitz, R., Alvarez, L., 2006. Piecewise-linearized cell transmission model and parameter calibration methodology. *Transportation Research Record: Journal of the Transportation Research Board* (1965), 183–191.
- Nanthawichit, C., Nakatsuji, T., Suzuki, H., 2003. Application of probe-vehicle data for real-time traffic-state estimation and short-term travel-time prediction on a freeway. *Transportation Research Record: Journal of the Transportation Research Board* 1855 (1), 49–59.
- Neumann, T., Bohnke, P.L., Tcheumadjeu, T., Louis, C., 2013. Dynamic representation of the fundamental diagram via Bayesian networks for estimating traffic flows from probe vehicle data, in: *2013 IEEE 16th International Conference on Intelligent Transportation Systems*, pp. 1870–1875.
- Newell, G.F., 1993a. A simplified theory of kinematic waves in highway traffic, part I: General theory. *Transportation Research Part B: Methodological* 27 (4), 281–287. doi:[10.1016/0191-2615\(93\)90038-C](https://doi.org/10.1016/0191-2615(93)90038-C).

- Newell, G.F., 1993b. A simplified theory of kinematic waves in highway traffic, part II: Queueing at freeway bottlenecks. *Transportation Research Part B: Methodological* 27 (4), 289–303. doi:[10.1016/0191-2615\(93\)90039-D](https://doi.org/10.1016/0191-2615(93)90039-D).
- Newell, G.F., 1993c. A simplified theory of kinematic waves in highway traffic, part III: Multi-destination flows. *Transportation Research Part B: Methodological* 27 (4), 305–313. doi:[10.1016/0191-2615\(93\)90040-H](https://doi.org/10.1016/0191-2615(93)90040-H).
- Newell, G.F., 2002. A simplified car-following theory: a lower order model. *Transportation Research Part B: Methodological* 36 (3), 195–205.
- Ngoduy, D., 2008. Applicable filtering framework for online multiclass freeway network estimation. *Physica A: Statistical Mechanics and its Applications* 387 (2), 599–616.
- Ngoduy, D., 2011. Kernel smoothing method applicable to the dynamic calibration of traffic flow models. *Computer-Aided Civil and Infrastructure Engineering* 26 (6), 420–432.
- Nguyen, V.T., Georges, D., Besançon, G., 2016. State and parameter estimation in 1-D hyperbolic PDEs based on an adjoint method. *Automatica* 67, 185–191. doi:[10.1016/j.automatica.2016.01.031](https://doi.org/10.1016/j.automatica.2016.01.031).
- Ni, D., Leonard II, J., 2005. Markov chain Monte Carlo multiple imputation using Bayesian networks for incomplete intelligent transportation systems data. *Transportation Research Record: Journal of the Transportation Research Board* (1935), 57–67.
- Panichpapiboon, S., Pattara-atikom, W., 2008. Evaluation of a neighbor-based vehicle density estimation scheme, in: 2008 8th International Conference on ITS Telecommunications, pp. 294–298.
- Papageorgiou, M., 1998. Some remarks on macroscopic traffic flow modelling. *Transportation Research Part A: Policy and Practice* 32 (5), 323–329. doi:[10.1016/S0965-8564\(97\)00048-7](https://doi.org/10.1016/S0965-8564(97)00048-7).
- Papageorgiou, M., Blosseville, J.M., Hadj-Salem, H., 1989. Macroscopic modelling of traffic flow on the Boulevard Périphérique in Paris. *Transportation Research Part B: Methodological* 23 (1), 29–47.
- Papageorgiou, M., Diakaki, C., Dinopoulou, V., Kotsialos, A., Wang, Y., 2003. Review of road traffic control strategies. *Proceedings of the IEEE* 91 (12), 2043–2067. doi:[10.1109/JPROC.2003.819610](https://doi.org/10.1109/JPROC.2003.819610).
- Pascale, A., Gomes, G., Nicoli, M., 2013. Estimation of highway traffic from sparse sensors: Stochastic modeling and particle filtering, in: 2013 IEEE International Conference on Acoustics, Speech and Signal Processing, pp. 6158–6162.
- Payne, H.J., 1971. Models of freeway traffic and control. *Mathematical Models of Public Systems* 1 (1), 51–61.
- Piccoli, B., Han, K., Friesz, T.L., Yao, T., 2013. Estimating fuel consumption and emissions via traffic data from mobile sensors, in: 2013 51st Annual Allerton Conference on Communication, Control, and Computing (Allerton), pp. 472–477. doi:[10.1109/Allerton.2013.6736562](https://doi.org/10.1109/Allerton.2013.6736562).
- Piccoli, B., Han, K., Friesz, T.L., Yao, T., Tang, J., 2015. Second-order models and traffic data from mobile sensors. *Transportation Research Part C: Emerging Technologies* 52, 32–56. doi:[10.1016/j.trc.2014.12.013](https://doi.org/10.1016/j.trc.2014.12.013).
- Polson, N., Sokolov, V., 2015. Bayesian analysis of traffic flow on interstate I-55: The LWR model. *The Annals of Applied Statistics* 9 (4), 1864–1888.
- Polson, N., Sokolov, V., 2016. Bayesian particle tracking of traffic flows, in: *Transportation Research Board 95th Annual Meeting*.
- Polson, N.G., Sokolov, V.O., 2017. Deep learning for short-term traffic flow prediction. *Transportation Research Part C: Emerging Technologies* 79, 1–17. doi:[10.1016/j.trc.2017.02.024](https://doi.org/10.1016/j.trc.2017.02.024).
- Pourmoallem, N., Nakatsuji, T., Kawamura, A., 1997. A neural-Kalman filtering method for estimating traffic states on freeways. *Journal of Infrastructure Planning and Managements* (569/IV-36), 105–114. doi:[10.2208/jscej.1997.569_105](https://doi.org/10.2208/jscej.1997.569_105).
- Qiu, T., Lu, X.Y., Chow, A., Shladover, S., 2010. Estimation of freeway traffic density with loop detector and probe vehicle data. *Transportation Research Record: Journal of the Transportation Research Board* (2178), 21–29.
- Ran, B., Tan, H., Wu, Y., Jin, P.J., 2016. Tensor based missing traffic data completion with spatial-temporal correlation. *Physica A: Statistical Mechanics and its Applications* 446, 54–63. doi:[10.1016/j.physa.2015.09.105](https://doi.org/10.1016/j.physa.2015.09.105).
- Richards, P.I., 1956. Shock waves on the highway. *Operations Research* 4 (1), 42–51.
- Sanwal, K.K., Walrand, J., 1995. Vehicles as probes. California Partners for Advanced Transit and Highways (PATH), Working Paper.
- Sau, J., El Faouzi, N.E., Assa, A.B., De Mouzon, O., 2007. Particle filter-based real-time estimation and prediction of traffic conditions. *Applied Stochastic Models and Data Analysis* 12.
- Schreier, T., Van Hinsbergen, C.P.I.J., Zuurbier, F.S., Van Lint, J.W.C., Hoogendoorn, S.P., 2010. Data-model synchronization in extended Kalman filters for accurate online traffic state estimation, in: *Proceedings of the Traffic Flow Theory Conference*.
- Seo, T., Kusakabe, T., 2015. Probe vehicle-based traffic state estimation method with spacing information and conservation law. *Transportation Research Part C: Emerging Technologies* 59, 391–403. doi:[10.1016/j.trc.2015.05.019](https://doi.org/10.1016/j.trc.2015.05.019).
- Seo, T., Kusakabe, T., Asakura, Y., 2015a. Estimation of flow and density using probe vehicles with spacing measurement equipment. *Transportation Research Part C: Emerging Technologies* 53, 134–150. doi:[10.1016/j.trc.2015.01.033](https://doi.org/10.1016/j.trc.2015.01.033).
- Seo, T., Kusakabe, T., Asakura, Y., 2015b. Traffic state estimation with the advanced probe vehicles using data assimilation, in: 2015 IEEE 18th International Conference on Intelligent Transportation Systems, pp. 824–830. doi:[10.1109/ITSC.2015.139](https://doi.org/10.1109/ITSC.2015.139).
- Seo, T., Kusakabe, T., Asakura, Y., 2016a. Calibration of fundamental diagram using trajectories of probe vehicles: Basic formulation and heuristic algorithm, in: *International Symposium of Transport Simulation and International Workshop on Traffic Data Collection and its Standardisation 2016*.
- Seo, T., Tchraïkian, T.T., Zhuk, S., Bayen, A.M., 2016b. Filter comparison for estimation on discretized PDEs modeling traffic: Ensemble Kalman filter and Minimax filter, in: 2016 IEEE 55th Conference on Decision and Control.
- Smith, B., Scherer, W., Conklin, J., 2003. Exploring imputation techniques for missing data in transportation management systems. *Transportation Research Record: Journal of the Transportation Research Board* (1836), 132–142.
- Song, H., Lee, H.S., 2013. A survey on vehicle density estimation in vehicular safety communications and its challenging issues, in: 2013 IEEE 16th International Conference on Intelligent Transportation Systems, pp. 2427–2432.
- Sumalee, A., Wang, J., Jedwanna, K., Suwansawat, S., 2012. Probabilistic fusion of vehicle features for reidentification and travel time estimation using video image data. *Transportation Research Record: Journal of the Transportation Research Board* 2308 (1), 73–82.
- Sumalee, A., Zhong, R.X., Pan, T.L., Szeto, W.Y., 2011. Stochastic cell transmission model (SCTM): A stochastic dynamic traffic model for traffic state surveillance and assignment. *Transportation Research Part B: Methodological* 45 (3), 507–533. doi:[10.1016/j.trb.2010.09.006](https://doi.org/10.1016/j.trb.2010.09.006).
- Sun, X., Muñoz, L., Horowitz, R., 2003. Highway traffic state estimation using improved mixture Kalman filters for effective ramp metering

- control, in: 2003 IEEE 42nd Conference on Decision and Control, pp. 6333–6338. doi:[10.1109/CDC.2003.1272322](https://doi.org/10.1109/CDC.2003.1272322).
- Sun, Y., Work, D.B., 2014. A distributed local Kalman consensus filter for traffic estimation, in: 2014 IEEE 53rd Conference on Decision and Control, pp. 6484–6491.
- Sun, Z., Jin, W.L., Ritchie, S.G., 2015. Simultaneous state and parameter estimation in Newell's simplified kinematic wave model with heterogeneous data, in: Transportation Research Board 94th Annual Meeting.
- Szeto, M.W., Gazis, D.C., 1972. Application of Kalman filtering to the surveillance and control of traffic systems. *Transportation Science* 6 (4), 419–439.
- Tak, S., Woo, S., Yeo, H., 2016. Data-driven imputation method for traffic data in sectional units of road links. *IEEE Transactions on Intelligent Transportation Systems* 17 (6), 1762–1771. doi:[10.1109/TITS.2016.2530312](https://doi.org/10.1109/TITS.2016.2530312).
- Tampère, C.M.J., Immers, L.H., 2007. An extended Kalman filter application for traffic state estimation using CTM with implicit mode switching and dynamic parameters, in: 2007 IEEE 10th International Conference on Intelligent Transportation Systems, pp. 209–216.
- Tan, H., Feng, G., Feng, J., Wang, W., Zhang, Y.J., Li, F., 2013. A tensor-based method for missing traffic data completion. *Transportation Research Part C: Emerging Technologies* 28, 15–27. doi:[10.1016/j.trc.2012.12.007](https://doi.org/10.1016/j.trc.2012.12.007).
- Tan, H., Wu, Y., Cheng, B., Wang, W., Ran, B., 2014. Robust missing traffic flow imputation considering nonnegativity and road capacity. *Mathematical Problems in Engineering* 2014.
- Tang, J., Zhang, G., Wang, Y., Wang, H., Liu, F., 2015. A hybrid approach to integrate fuzzy C-means based imputation method with genetic algorithm for missing traffic volume data estimation. *Transportation Research Part C: Emerging Technologies* 51, 29–40. doi:[10.1016/j.trc.2014.11.003](https://doi.org/10.1016/j.trc.2014.11.003).
- Tchraikian, T.T., Zhuk, S., 2015. A macroscopic traffic data-assimilation framework based on the Fourier–Galerkin method and minimax estimation. *IEEE Transactions on Intelligent Transportation Systems* 16 (1), 452–464. doi:[10.1109/TITS.2014.2347415](https://doi.org/10.1109/TITS.2014.2347415).
- Tchraikian, T.T., Zhuk, S., Nogueira, A.C., 2015. Robust traffic density estimation using discontinuous Galerkin formulation of a macroscopic model, in: 2015 IEEE 18th International Conference on Intelligent Transportation Systems, pp. 2147–2152.
- Thai, J., Bayen, A.M., 2015. State estimation for polyhedral hybrid systems and applications to the Godunov scheme for highway traffic estimation. *IEEE Transactions on Automatic Control* 60 (2), 311–326.
- Timotheou, S., Panayiotou, C.G., Polycarpou, M.M., 2015a. Moving horizon fault-tolerant traffic state estimation for the cell transmission model, in: 2015 IEEE 54th Conference on Decision and Control, pp. 3451–3456. doi:[10.1109/CDC.2015.7402753](https://doi.org/10.1109/CDC.2015.7402753).
- Timotheou, S., Panayiotou, C.G., Polycarpou, M.M., 2015b. Transportation systems: Monitoring, control, and security, in: *Intelligent Monitoring, Control, and Security of Critical Infrastructure Systems*. Springer, pp. 125–166.
- Traffic Flow Theory and Characteristics Committee (Ed.), 2011. 75 Years of the Fundamental Diagram for Traffic Flow Theory: Greenshields Symposium. Transportation Research Board.
- Treiber, M., Helbing, D., 2002. Reconstructing the spatio-temporal traffic dynamics from stationary detector data. *Cooperative Transport Dynamics* 1 (3), 3.1–3.24.
- Treiber, M., Kesting, A., 2013. *Traffic Flow Dynamics: Data, Models and Simulation*. Springer Berlin Heidelberg. doi:[10.1007/978-3-642-32460-4](https://doi.org/10.1007/978-3-642-32460-4).
- Treiber, M., Kesting, A., Wilson, R.E., 2011. Reconstructing the traffic state by fusion of heterogeneous data. *Computer-Aided Civil and Infrastructure Engineering* 26 (6), 408–419.
- US Department of Transportation, 2006. NGSIM—Next Generation Simulation. <http://ops.fhwa.dot.gov/trafficanalysisistools/ngsim.htm>, accessed: 2015-02-10.
- Van Leeuwen, P.J., Cheng, Y., Reich, S., 2015. *Nonlinear Data Assimilation*. volume 2. Springer.
- Vivas, C., Siri, S., Ferrara, A., Sacone, S., Cavanna, G., Rubio, F.R., 2015. Distributed consensus-based switched observers for freeway traffic density estimation, in: 2015 IEEE 54th Conference on Decision and Control, pp. 3445–3450. doi:[10.1109/CDC.2015.7402672](https://doi.org/10.1109/CDC.2015.7402672).
- Vlahogianni, E.I., Karlaftis, M.G., Golias, J.C., 2014. Short-term traffic forecasting: Where we are and where we're going. *Transportation Research Part C: Emerging Technologies* 43, 3–19. doi:[10.1016/j.trc.2014.01.005](https://doi.org/10.1016/j.trc.2014.01.005).
- Wada, K., Usui, K., Takigawa, T., Kuwahara, M., 2017. An optimization modeling of coordinated traffic signal control based on the variational theory and its stochastic extension, in: *The 22nd International Symposium on Transportation and Traffic Theory*.
- van Wageningen-Kessels, F., van Lint, H., Vuik, K., Hoogendoorn, S., 2014. Genealogy of traffic flow models. *EURO Journal on Transportation and Logistics* 4 (4), 445–473. doi:[10.1007/s13676-014-0045-5](https://doi.org/10.1007/s13676-014-0045-5).
- Wang, R., Fan, S., Work, D.B., 2016a. Efficient multiple model particle filtering for joint traffic state estimation and incident detection. *Transportation Research Part C: Emerging Technologies* 71, 521–537. doi:[10.1016/j.trc.2016.08.003](https://doi.org/10.1016/j.trc.2016.08.003).
- Wang, R., Work, D.B., 2014. Interactive multiple model ensemble Kalman filter for traffic estimation and incident detection, in: 2014 IEEE 17th International Conference on Intelligent Transportation Systems, pp. 804–809.
- Wang, R., Work, D.B., Sowers, R., 2016b. Multiple model particle filter for traffic estimation and incident detection. *IEEE Transactions on Intelligent Transportation Systems* doi:[10.1109/TITS.2016.2560769](https://doi.org/10.1109/TITS.2016.2560769).
- Wang, Y., Papageorgiou, M., 2005. Real-time freeway traffic state estimation based on extended Kalman filter: a general approach. *Transportation Research Part B: Methodological* 39 (2), 141–167. doi:[10.1016/j.trb.2004.03.003](https://doi.org/10.1016/j.trb.2004.03.003).
- Wang, Y., Papageorgiou, M., Messmer, A., 2006. RENAISSANCE — a unified macroscopic model-based approach to real-time freeway network traffic surveillance. *Transportation Research Part C: Emerging Technologies* 14 (3), 190–212. doi:[10.1016/j.trc.2006.06.001](https://doi.org/10.1016/j.trc.2006.06.001).
- Wang, Y., Papageorgiou, M., Messmer, A., Coppola, P., Tzimitsi, A., Nuzzolo, A., 2009. An adaptive freeway traffic state estimator. *Automatica* 45 (1), 10–24. doi:[10.1016/j.automatica.2008.05.019](https://doi.org/10.1016/j.automatica.2008.05.019).
- Wardrop, J.G., Charlesworth, G., 1954. A method of estimating speed and flow of traffic from a moving vehicle, in: *ICE Proceedings: Engineering Divisions*, pp. 158–171.
- Wasson, J.S., Sturdevant, J.R., Bullock, D.M., 2008. Real-time travel time estimates using media access control address matching. *ITE Journal* 78 (6).
- White, J., Wells, I., 2002. Extracting origin destination information from mobile phone data, in: *Eleventh International Conference on Road Transport Information and Control*, pp. 30–34.

- Whitham, G.B., 1974. *Linear and Nonlinear Waves*. John Wiley & Sons.
- Wilby, M.R., Diaz, J.J.V., Gonzalez, A.B.R., Sotelo, M.A., 2014. Lightweight occupancy estimation on freeways using extended floating car data. *Journal of Intelligent Transportation Systems* 18 (2), 149–163. doi:[10.1080/15472450.2013.801711](#).
- Wilkie, D., Sewall, J., Lin, M., 2013. Flow reconstruction for data-driven traffic animation. *ACM Transactions on Graphics (TOG)* 32 (4), 89:1–89:10.
- Wong, G.C.K., Wong, S.C., 2002. A multi-class traffic flow model—an extension of LWR model with heterogeneous drivers. *Transportation Research Part A: Policy and Practice* 36 (9), 827–841.
- Work, D.B., Blandin, S., Tossavainen, O.P., Piccoli, B., Bayen, A.M., 2010. A traffic model for velocity data assimilation. *Applied Mathematics Research eXpress* 2010 (1), 1–35.
- Work, D.B., Tossavainen, O.P., Blandin, S., Bayen, A.M., Iwuchukwu, T., Tracton, K., 2008. An ensemble Kalman filtering approach to highway traffic estimation using GPS enabled mobile devices, in: 2008 IEEE 47th Conference on Decision and Control, pp. 5062–5068. doi:[10.1109/CDC.2008.4739016](#).
- Wright, M., Horowitz, R., 2016. Fusing loop and GPS probe measurements to estimate freeway density. *IEEE Transactions on Intelligent Transportation Systems* 17 (12), 3577–3590. doi:[10.1109/TITS.2016.2565438](#).
- Wu, C., Thai, J., Yablowsky, S., Pozdnoukhov, A., Bayen, A.M., 2015. Cellpath: Fusion of cellular and traffic sensor data for route flow estimation via convex optimization. *Transportation Research Part C: Emerging Technologies* 59, 111–128. doi:[10.1016/j.trc.2015.05.004](#).
- Xia, C., Cochrane, C., DeGuire, J., Fan, G., Holmes, E., McGuirl, M., Murphy, P., Palmer, J., Carter, P., Slivinski, L., Sandstede, B., 2017. Assimilating Eulerian and Lagrangian data in traffic-flow models. *Physica D: Nonlinear Phenomena* doi:[10.1016/j.physd.2017.02.004](#).
- Xu, D.W., Dong, H.H., Li, H.J., Jia, L.M., Feng, Y.J., 2015. The estimation of road traffic states based on compressive sensing. *Transportmetrica B: Transport Dynamics* 3 (2), 131–152. doi:[10.1080/21680566.2014.963736](#).
- Yang, J., Sun, J., 2015. Vehicle path reconstruction using automatic vehicle identification data: An integrated particle filter and path flow estimator. *Transportation Research Part C: Emerging Technologies* 58, 107–126.
- Yin, W., Murray-Tuite, P., Rakha, H., 2012. Imputing erroneous data of single-station loop detectors for nonincident conditions: comparison between temporal and spatial methods. *Journal of Intelligent Transportation Systems* 16 (3), 159–176.
- Yuan, Y., 2013. Lagrangian multi-class traffic state estimation. Ph.D. thesis. Delft University of Technology.
- Yuan, Y., van Lint, J.W.C., Wilson, R.E., van Wageningen-Kessels, F., Hoogendoorn, S.P., 2012. Real-time Lagrangian traffic state estimator for freeways. *IEEE Transactions on Intelligent Transportation Systems* 13 (1), 59–70.
- Yuan, Y., Scholten, F., van Lint, H., 2015. Efficient traffic state estimation and prediction based on the ensemble Kalman filter with a fast implementation and localized deterministic scheme, in: 2015 IEEE 18th International Conference on Intelligent Transportation Systems, pp. 477–482.
- Yuan, Y., Van Lint, H., Van Wageningen-Kessels, F., Hoogendoorn, S., 2014. Network-wide traffic state estimation using loop detector and floating car data. *Journal of Intelligent Transportation Systems* 18 (1), 41–50. doi:[10.1080/15472450.2013.773225](#).
- Zhang, H.M., 2002. A non-equilibrium traffic model devoid of gas-like behavior. *Transportation Research Part B: Methodological* 36 (3), 275–290. doi:[10.1016/S0191-2615\(00\)00050-3](#).
- Zhang, L., Mao, X., 2015. Vehicle density estimation of freeway traffic with unknown boundary demand–supply: an interacting multiple model approach. *IET Control Theory Applications* 9 (13), 1989–1995. doi:[10.1049/iet-cta.2014.1251](#).
- Zheng, Z., Su, D., 2016. Traffic state estimation through compressed sensing and Markov random field. *Transportation Research Part B: Methodological* 91, 525–554. doi:[10.1016/j.trb.2016.06.009](#).
- Zhong, M., Lingras, P., Sharma, S., 2004. Estimation of missing traffic counts using factor, genetic, neural, and regression techniques. *Transportation Research Part C: Emerging Technologies* 12 (2), 139–166.
- Zhong, R., Chen, C., Chow, A.H.F., Pan, T., Yuan, F., He, Z., 2015. Automatic calibration of fundamental diagram for first-order macroscopic freeway traffic models. *Journal of Advanced Transportation* 50 (3), 363–385. doi:[10.1002/atr.1334](#).
- Zito, R., D’Este, G., Taylor, M.A.P., 1995. Global positioning systems in the time domain: How useful a tool for intelligent vehicle-highway systems? *Transportation Research Part C: Emerging Technologies* 3 (4), 193–209. doi:[10.1016/0968-090X\(95\)00006-5](#).
- Zuurbier, F.S., van Lint, J.W.C., Knoop, V., 2006. Traffic network state estimation using extended Kalman filtering and DSMT, in: The 11th IFAC Symposium on Control in Transportation Systems.