T2R2 東京科学大学 リサーチリポジトリ Science Tokyo Research Repository

論文 / 著書情報 Article / Book Information

題目(和文)	 機構学的等価機構による低自由度パラレルマニピュレータの運動解析 と設計		
Title(English)	Kinematic Analysis and Design of Lower-mobility Parallel Manipulator Based on Kinematically Equivalent Mechanism		
著者(和文)	梁 星海		
Author(English)	Xinghai Liang		
出典(和文)	学位:博士(工学), 学位授与機関:東京工業大学, 報告番号:甲第11268号, 授与年月日:2019年9月20日, 学位の種別:課程博士, 審査員:武田 行生,岩附 信行,岡田 昌史,遠藤 玄,菅原 雄介		
Citation(English)	Degree:Doctor (Engineering), Conferring organization: Tokyo Institute of Technology, Report number:甲第11268号, Conferred date:2019/9/20, Degree Type:Course doctor, Examiner:,,,,		
学位種別(和文)			
Category(English)	Doctoral Thesis		
種別(和文)	 論文要旨 		
Type(English)	Summary		

論 文 要 旨

THESIS SUMMARY

系・コース: Department of, Graduate major in	機械 機械	系 コース	申請学位(専攻分野): Academic Degree Requested	博士 (工学) Doctor of
学生氏名:	LIANG Xinghai		指導教員(主):	武田 行生
Student's Name			Academic Supervisor(main)	
			指導教員(副):	杏百 雄介
			Academic Supervisor(sub)	自 /示 4年/1

要旨(英文800語程度)

Thesis Summary (approx.800 English Words)

The kinematic analysis and design processes of the lower-mobility parallel manipulators (LMPM) usually focus on symmetric structures, such as all the kinematic chains are identical, base and moving platform are central symmetric or line symmetric. The reason is because the LMPM with symmetric structure has isotropic mobility, which is adaptable to different kinds of tasks. On the other hand, LMPM with asymmetric structure or non-identical chains may have advantages when the task is clearly specified. Therefore, regarding the kinematic analysis and design processes of the LMPM with 3-RS and 3-SR structures, a unified model considering both chain types (e.g. <u>PRS</u>, <u>PSR</u>, <u>RRS</u>, and so on) and various structural parameters will be a convenient tool.

However, the conventional analytical methods based the constraint equations for solving inverse kinematics (IK) of this class of LMPMs are derived from the specific geometric parameters and configurations, such as the configuration where three identical kinematic chains are symmetrically arranged. In addition, the constraint equations are restricted to the choice of the independent pose parameters. As a result, if the configuration or parameters of the mechanism change, the methods may not be suitable, or the constraint equations need to be reformulated. In other words, the analytical expressions of the solutions of the IK are limited to the structural and dimensional conditions, from which constraint equations leading to the closed-form equations are derived, such as the kinematic chain architecture, geometric relationship among joints, and the values of the geometric parameters. Therefore, it is technically difficult to build such a unified model using conventional analytical method.

Furthermore, due to the complex structures of parallel manipulators, there is no universal and simple index that accurately representing the kinematic performance of all types of parallel manipulators. Developing suitable kinematic performance metrics for parallel manipulators remains an issue. To the best of my knowledge, there have been no performance index considering the characteristics of the RS chain.

This thesis focuses on the kinematic analysis and design of the class of LMPM, a type of 3-degrees-of-freedom (DOF) parallel manipulators composed of a base and a moving platform with three kinematic chain connecting them. The feature of this class of lower-mobility parallel manipulators is that they become a 3-RS (or 3-SR) structure after locking all the actuators, which is simply termed "primary structure" in the thesis.

Firstly, an idea, kinematically equivalent mechanism (KEM), is proposed. Kinematically equivalent mechanism is able to reflect the practical force transmission and constraint characteristics of an R joint composed of two bearings in the corresponding lower-mobility parallel manipulator, while the motion and constraint characteristics of the kinematically equivalent mechanism are the same as those of the corresponding manipulator once certain actuated joints motion constraints are satisfied.

Secondly, an iterative method for solving the inverse kinematics of lower-mobility parallel manipulators based on the kinematically equivalent mechanism is proposed. The method enables to solve the inverse kinematics of such parallel manipulators considering various structural parameters and different sets of output DOFs in a unified modelling, yet without formulating conventional constraint equations. The process in solving the IK of the LMPMs considering different sets of output DOFs and various structural parameters using the proposed method are demonstrated by numerical examples.

Next, an intuitive approach to evaluate the kinematic performance of a parallel manipulator is proposed. The proposed transmission index (TI) is based on the pressure angle of the kinematically equivalent mechanism. The proposed TI can be used in not only lower-mobility parallel manipulators but also hybrid parallel manipulators where two actuators exist in each kinematic chain. The proposed approach can indicate both output and constraint singularity conditions with a single index, through simple calculation process without complicated normalization, and can include the width of the revolute joint in the kinematic performance evaluation of this class of parallel manipulators. The effectiveness of TI

is verified by numerical examples, such as the singularity analysis, relationships between the maximum joint forces and index values, distribution of TI inside the workspace.

Finally, a methodology of kinematic performance analysis and design of the lower-mobility parallel manipulator is proposed based on the iterative method for solving inverse kinematics and TI. The kinematic performance is evaluated by the criteria such as the reachable orientation workspace (ROW), global transmission index (GTI), parasitic motion, and good performance orientation workspace (GPOW). The features of the proposed analysis method are shown by numerical results. A multi-objective optimization for a 3-<u>P</u>RS parallel manipulator based on genetic algorithm is implemented and design examples are shown and discussed.

備考 : 論文要旨は、和文 2000 字と英文 300 語を1 部ずつ提出するか、もしくは英文 800 語を1 部提出してください。

Note : Thesis Summary should be submitted in either a copy of 2000 Japanese Characters and 300 Words (English) or 1 copy of 800 Words (English).

注意:論文要旨は、東工大リサーチリポジトリ(T2R2)にてインターネット公表されますので、公表可能な範囲の内容で作成してください。 Attention: Thesis Summary will be published on Tokyo Tech Research Repository Website (T2R2).