

論文 / 著書情報
Article / Book Information

題目(和文)	
Title(English)	Study on the Influence of the Inlet Swirling Flow in a Double and Triple Elbow Using Phased Array UVP
著者(和文)	SanShwin
Author(English)	San Shwin
出典(和文)	学位:博士(工学), 学位授与機関:東京工業大学, 報告番号:甲第11018号, 授与年月日:2018年12月31日, 学位の種別:課程博士, 審査員:木倉 宏成,加藤 之貴,赤塚 洋,筒井 広明,相樂 洋
Citation(English)	Degree:Doctor (Engineering), Conferring organization: Tokyo Institute of Technology, Report number:甲第11018号, Conferred date:2018/12/31, Degree Type:Course doctor, Examiner:,,,,
学位種別(和文)	博士論文
Category(English)	Doctoral Thesis
種別(和文)	論文要旨
Type(English)	Summary

論文要旨

THESIS SUMMARY

専攻 : Department of	Nuclear Engineering	専攻	申請学位 (専攻分野) : Academic Degree Requested	博士 Doctor of	(Engineering)
学生氏名 : Student's Name	San Shwin		指導教員 (主) : Academic Supervisor(main)	Hiroshige Kikura	
			指導教員 (副) : Academic Supervisor(sub)	Hiroshi Akatsuka	

要旨 (英文 800 語程度)

Thesis Summary (approx.800 English Words)

In the introduction part, the turbulent swirling flow structure in the bend pipe or the elbow are discussed from the viewpoint of the previous studies and the history of pipe break accident in the piping system of the power plant. The primary objectives of this dissertation and the outline of each chapter are written in the introduction part. The developing process of ultrasound technique is describe to provide the information of the measurement system.

The fluid velocity measurements in a circular straight pipe are carried out using UVP system. The fully develop region can be observed for the turbulent flow at several Reynolds number. The velocity profiles from the measurement results are imposed as the inlet boundary condition for a single elbow simulation using CFD Fluent 16.2. The basic flow theory of turbulent flow in a single elbow pipe is mentioned in this chapter. The fluid flow structure and turbulent intensity are analyzed base on the different Reynolds number downstream of a single elbow. From this investigation, the appropriate Reynolds number is choice to use in the next chapter of the turbulent flow measurement and inlet swirling flow measurement.

In the condition of turbulent flow, two-dimensional velocity fields are investigated downstream of double bend pipe, which made by 90° double elbow. Particle Image Velocimetry and Phased Array UVP systems are applied to compare the measurement results. The flow distortion and recirculating flow occur in the measurement region downstream of the double elbow. The reverse secondary flow region and the reattachment point is clearly observed from both measurement results. In the velocity fluctuation analysis, the axial velocity fluctuation apparently occurs at the boundary of the main flow and the recirculating flow. The radial velocity fluctuation occurs at the center of the pipe.

The influence of inlet swirling flow on the flow structure and velocity fluctuation downstream of double bend pipe layout, which made by 90° double elbow is observed with inlet swirling flow and without inlet swirling flow condition. Phased Array UVP measurement done in the case of with and without inlet swirling flow condition. The inlet swirling flow is confirmed by measuring the cross-section plane 7D downstream of the swirling generator in the condition of swirl intensity $S = 1$. The swirling generator generates the homogeneous swirling flow. The experiment results of one-dimensional normalized axial and tangential velocity with their standard deviations in four positions downstream of the double bend pipe with and without inlet swirling flow. According to one-dimensional velocity profiles, the velocity magnitude of inlet swirling flow is much stronger than without inlet swirling flow in the secondary flow region. These differences are due to the influence of the inlet swirling flow. In two-dimensional velocity of without inlet swirling flow, the flow separation occurs around $x/D = 0.1$, and the reattachment point is located at $x/D = 1.5$. In case of inlet swirling flow, the flow separation phenomenon is same as the condition of without inlet swirling flow, but the reattachment point is located at $x/D = 1$. Therefore, the reverse flow region is narrow. At $x/D = 1.5$, the fluid becomes the accelerated swirling flow. In the condition of without inlet swirling flow, the axial velocity fluctuation is higher than with inlet swirling flow, but tangential velocity fluctuation is lower than inlet swirling flow.

The experimental investigation and numerical simulation were done to observe the flow structure and velocity distribution at the inlet swirling flow condition. The axial, radial and tangential velocities of the swirling flow were measured at 7D downstream of the swirling generator by using a phased array sensor. The sensor position was turned into the axial and cross-sectional planes to get the axial, radial and tangential velocities. The velocities were utilized for the boundary inlet conditions of the numerical simulation. The inlet swirling flow velocities from the experimental results were utilized to compare with experimental result and validate CFD numerical

simulation. We used the axial, radial and tangential velocity profiles of swirling flow as the inlet boundary conditions and the geometry of the pipe layout was same as the experimental setup. In addition, Phased Array UVP system is applied to measure two-dimensional velocity field downstream of the triple elbow in order to can confirm the flow separation and reattachment point in the reverse flow region. The numerical simulation result show that the swirling flow structure is quite similar with the experimental result. Therefore, the validation of the CFD simulation is acceptable. In case of cross-sectional plane visualization, two counter rotation vortex cells were observed at $x/D = 0.2$ and $x/D = 0.6$ positions. When the high velocity axial flow reached the outside wall, this flow was changed from outside to lateral side of pipe wall in clockwise and counterclockwise directions. In addition, the axial velocity distribution is too different between the intrados and extrados of pipe.

備考：論文要旨は、和文 2000 字と英文 300 語を 1 部ずつ提出するか、もしくは英文 800 語を 1 部提出してください。

Note : Thesis Summary should be submitted in either a copy of 2000 Japanese Characters and 300 Words (English) or 1copy of 800 Words (English).

注意：論文要旨は、東工大リサーチリポジトリ (T2R2) にてインターネット公表されますので、公表可能な範囲の内容で作成してください。

Attention: Thesis Summary will be published on Tokyo Tech Research Repository Website (T2R2).