

論文 / 著書情報
Article / Book Information

題目(和文)	
Title(English)	3D Shape and Spectral Reflectance Estimation Using Off-the-Shelf Camera and Projector
著者(和文)	李淳雨
Author(English)	Chunyu Li
出典(和文)	学位:博士(工学), 学位授与機関:東京工業大学, 報告番号:甲第11747号, 授与年月日:2022年3月26日, 学位の種別:課程博士, 審査員:奥富 正敏,蜂屋 弘之,塚越 秀行,原 精一郎,田中 正行
Citation(English)	Degree:Doctor (Engineering), Conferring organization: Tokyo Institute of Technology, Report number:甲第11747号, Conferred date:2022/3/26, Degree Type:Course doctor, Examiner:,,,,
学位種別(和文)	博士論文
Category(English)	Doctoral Thesis
種別(和文)	論文要旨
Type(English)	Summary

論文要旨

THESIS SUMMARY

系・コース： システム制御 系
Department of Graduate major in システム制御 コース
学生氏名： 李 淳雨
Student's Name

申請学位 (専攻分野)： 博士 (工学)
Academic Degree Requested Doctor of
指導教員 (主)： 奥富 正敏
Academic Supervisor(main)
指導教員 (副)：
Academic Supervisor(sub)

要旨 (英文 800 語程度)

Thesis Summary (approx.800 English Words)

Image-based reconstruction of an object's 3D shape having the wavelength-by-wavelength spectral reflectance property enables higher-fidelity object 3D modeling compared with typical RGB-based modeling. This thesis proposes a novel method for practical and low-cost acquisition of a dense object 3D model with the spectral reflectance property. Different from existing spectral 3D data acquisition systems that use a dedicated multispectral camera or light, we use a standard RGB camera and an off-the-shelf light source device as active illumination for both the 3D reconstruction and the spectral reflectance estimation.

Chapter 1, Introduction - This chapter introduces the background and applications of 3D reconstruction and the spectral reflectance estimation. 3D reconstruction and spectral reflectance estimation are well-studied research topics in computer vision. However, these two research fields have progressed separately. So in this chapter, we separately review the previous works related to 3D reconstruction and spectral reflectance estimation, and discusses the weakness of previous works from the viewpoints of the accuracy, the convenience for use, and the cost.

Chapter 2, Pro-Cam SSfM: 3D Shape and Spectral Reflectance Estimation Using Structured-light and Uniform Color Illuminations - In this chapter, we first propose a novel projector-camera system called Pro-Cam SSfM, for structure and spectral reflectance from motion. In Pro-Cam SSfM, we use a standard RGB camera and leverage an off-the-shelf projector for two roles: structured light and multispectral imaging. For our data acquisition, structured light patterns (for geometric observations) and uniform color illuminations (for multispectral observations) are sequentially projected onto the object surface while alternately moving the camera and the projector to arbitrary positions around the object. Using the captured multi-view structured light data, we first reconstruct the dense 3D points of the whole shape while estimating the poses of all moved cameras and projectors in a self-calibration manner based on SfM using the tracked feature correspondences among all the projector and the camera viewpoints. Using the captured multi-view multispectral data, we then estimate the spectral reflectance of each 3D point considering the geometric relationship between the reconstructed 3D points and the estimated projector positions. Owing to the proposed self-calibrating 3D reconstruction, the reconstructed 3D points and the estimated projector positions can be used to construct a lighting model to eliminate the baked-in effect of the shading and the shadows from the estimated spectral reflectance without requiring any geometric calibration.

Chapter 3, Spectral MVIR: Joint Optimization of 3D Shape and Spectral Reflectance - In contrast to the separate estimation of 3D shape and spectral reflectance for Pro-Cam SSfM (Chapter 2), we propose a novel Multi-View Inverse Rendering (MVIR) method called Spectral MVIR for jointly reconstructing the detailed 3D shape and the spectral reflectance for each point of object surfaces from multi-view images. Unlike Pro-Cam SSfM, Spectral MVIR has no limitation of the selection on lighting devices. Spectral MVIR is suitable to a setup that using a low-cost smart LED bulb as light source. The smart LED bulb can emit several types of illumination with different spectral power distributions. (Note that, instead of a smart LED bulb, we can use separate light sources with arbitrary positions for our method.) Using the captured input images, we first estimate camera poses and an initial mesh model based on SfM and MVS, and then jointly optimize each vertex's 3D position and spectral reflectance by minimizing multi-view and multispectral rendering errors. Spectral MVIR can also be directly applied to the initial 3D model obtained by Pro-Cam SSfM to refine 3D model via the joint optimization exploiting the shading information observed by the camera, which has a much higher pixel resolution than the projector.

Chapter 4, *Learning-Based Single-Shot Estimation Using Color-Dot Projection* - These 3D spectral acquisition methods introduced in previous chapters observe spectral measurements by temporally changing illumination spectrum, thus they are limited to static scenes and not applicable to dynamic scenes. In this chapter, we propose a novel single-shot system to simultaneously acquire the depth and the spectral reflectance using a standard RGB camera and an off-the-shelf projector. Our system is based on a single random color-dot projection, which simultaneously acts as structured light for depth reconstruction and spatially-varying color illuminations for spectral reconstruction. Since the random color dot provides a unique code pattern and three distinct RGB color illuminations for each local region, we exploit these cues for the depth and the spectral reconstruction. To effectively reconstruct the depth and the spectral reflectance from a single color-dot image, we propose a novel end-to-end deep learning method. Since the location of the observed color-dot pattern depends on the scene depth, we perform the joint learning of the depth and the spectral reflectance to improve the accuracy of each other, by considering the geometric warping of the color-dot pattern. Furthermore, to address the difficulty of constructing a real-world hyperspectral-depth dataset, we develop a spectral renderer to generate a synthetic dataset using a spectral rendering model under the color-dot illumination.

Chapter 5, *Conclusions and Future Works* - This chapter concludes the key ideas, combs the dissertation, and outlines possible future directions of the works.

備考：論文要旨は、和文 2000 字と英文 300 語を 1 部ずつ提出するか、もしくは英文 800 語を 1 部提出してください。

Note : Thesis Summary should be submitted in either a copy of 2000 Japanese Characters and 300 Words (English) or 1copy of 800 Words (English).

注意：論文要旨は、東工大リサーチリポジトリ(T2R2)にてインターネット公表されますので、公表可能な範囲の内容で作成してください。

Attention: Thesis Summary will be published on Tokyo Tech Research Repository Website (T2R2).